

Section 1. Product and Company Identification.

1.1 Model Number; LED191T v1

1.2 Description; Rechargeable Floodlight 30W SMD Folding Case

Battery: 7.4 Volts. 8.8 Ah.

1.3 Manufacturer;

Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 30 April 2014

Section 2. Hazards Identification.

Invasion Routes: Eyes, skin contact, ingestion.

Health Hazard: Harmful if swallowed. Safe under normal conditions of use. Contents are non-reactive when the battery integrity and seals remain intact. DO NOT OPEN or DISMANTLE. DO NOT EXPOSE TO FIRE or NAKED FLAME.

Burn / Explosion / Fire risks: do not mix with varying chemistries, sizes & types of battery.

Burn / Explosion / Fire risks; do not mix with varying chemistries, sizes & types of battery.

Do not crush or incinerate.

Environmental Hazard: The internal electrolyte may cause adverse environmental impact. **Danger of Fire and Explosion:** Risk is increased by high temperature and short circuit.



Section 3. Substances.

			Classification	
2 1 Chamical Name (substance)	3.1 CAS No.	3.2 Concentration	Hazard Class &	Hazard
3.1 Chemical Name (substance)	5.1 CAS NO.	Weight	Category Code	Statements
Lithium Nickel Cobalt Manganese Oxide	-	41%	-	-
Graphite	7782-42-5	20%	Skin Irrit. 2	H315
			Eye Irrit. 2	H319
			STOT SE 3	H335
Copper Foil	7440-50-8	20%	Acute Tox. 4	H302
			Skin Irrit. 2	H315
			Eye Irrit. 2	H319
			Acute Tox. 4	H332
			STOT SE 3	H335
			Aquatic Acute 1	H400
			Aquatic Chronic 1	H410
Aluminium Foil	7429-90-5	10%	Water-react. 2	H261
			Flam. Sol. 3	H250
Polyvinylidene Fluoride	24937-79-9	10%	Skin Irrit. 2	H315
			Eye Irrit. 2	H319
			STOT SE 3	H335
PE/PP Film	-	3%	-	-
Carbonaceous Additive	-	1.1%	-	-

For full text of Phrases and Statements, see Section 16.



Section 4. First Aid Measures.

Lithium Batteries do not pose a risk to eyes or skin under normal circumstances. In the case of contact with internal substances;

4.1 Description of first aid measures

Inhalation

If breathing difficulties develop, remove the person to fresh air.

Loosen close fitting clothing.

Ensure that person is warm.

If mouth to mouth resuscitation is necessary, the person conducting this must takes steps to reduce the risk of contamination from toxic / corrosive substances that may be present.

Skin Contact

Remove contaminated clothing.

Flush affected area(s) with copious amounts of water for at least 15 minutes.

Get medical attention.

Eye Contact

Irrigate eyes with water for at least 15 minutes while raising eyelid(s).

Get medical attention.

Ingestion

If swallowed, do not induce vomiting. Give large amounts of water but do not do this is casualty is unconscious.

Protection of First Aiders:

Use personal protective equipment. Avoid contact with skin, eyes and clothing.

4.2. Most important symptoms and effects, both acute and delayed No information available.

4.3. Indication of any immediate medical attention and special treatment needed No information available.



Section 5. Fire Fighting Measures.

Recommended practice;

Always ensure that Personal Protection Equipment (PPE) is used.

If a battery becomes hot, immediately remove it from flammable materials and place on a non-combustible surface. If possible, place a disintegrating device outdoors and allow it to burn out.

Fire condition; NB; ensure that electrical devices are turned off. Prevent electric shock risk.

If any batteries are burning, water may not extinguish them, but will cool the adjacent batteries and control the spread of fire.

5.1. Extinguishing media

Extinguishers;

Only use Graphite based CO₂ (Carbon dioxide), Dry Powder or Foam.

Copper powder fire extinguishers, sand, dry ground dolomite or soda ash may also be used. These materials act as smothering agents.

If possible, use a **LITH-X (powdered graphite)** extinguisher on small fires. This material acts as a smothering agent. A **sodium chloride powder** extinguisher **IS NOT** suitable for use on Lithium Batteries.

It may not be possible to extinguish burning lithium batteries. Burning batteries will burn themselves out. <u>Do not use water</u> with **LITH-X** (powdered graphite).

If a LITH-X (powdered graphite) extinguisher is not available;

Use copious amounts of water in a fine spray to swamp a fire.

Continue to use copious amounts of water until the fire is extinguished and the batteries are cooled.

NB: **Lithium reacts with water to form Hydrogen.** The fire will not be extinguished immediately. Be aware of the increased risk of explosion.

NB; fire-fighting water runoff may be corrosive / toxic and may cause adverse environmental impact.

5.2. Special hazards arising from the substance or mixture

Hazard characteristics; thermal decomposition can lead to the release of toxic fumes.

Hazardous combustion products; carbon dioxide, carbon monoxide, lithium oxide fumes.

5.3. Advice for fire-fighters

Fragments may be ejected from a fire.

Fire Fighters should wear self-contained breathing apparatus and appropriate Personal Protective Equipment.



Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures In the event of battery rupture and leakage,

- Ventilate the area.
- Wear appropriate protective clothing (see Section 7) to prevent eye and skin contact and to prevent inhalation of vapours or fumes.
- Remove sources of ignition.

6.2. Environmental precautions

No information available.

6.3. Methods and material for containment and cleaning up

Absorb released materials with inert absorbent (dry sand or soil).

Collect released materials into sealed plastic bag or container.

Prevent material from contaminating soil or entering sewers or waterways.

Do not dispose of released materials with domestic waste

Do not allow product to enter ground water, water course or sewerage system.

Dispose of released materials in accordance with local authority regulations.

6.4. Reference to other sections

See Section 7 for information on Safe Handling

See Section 8 for information of Personal Protective Equipment.

See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling

Never dismantle or modify a battery.

Do not short circuit a battery. A short circuit causes heating and can lead to ignition of surrounding materials.

Physical contact with a short-circuited battery can cause skin burn.

When charging the battery, use dedicated chargers and follow the specified conditions.

Improperly charging a battery may cause the battery to combust.

Lithium batteries for transport by air in a state of charge must have no more than 30% charge of their rated capacity.

7.2. Conditions for safe storage, including any incompatibilities

Always store batteries in an appropriate container to prevent contact with conductive materials.

Do not allow contact with water.

Store in original container. Keep container tightly closed.

Store in a dry, cool place.

Store at 20 °C (68°F); room temperature

Store away from ignition sources, heat, and incompatible materials.

7.3. Specific end use(s)

Intended for use as the battery for the Model Number identified in 1.1 with Description stated in 1.2



Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters

In the event of battery rupture and leakage:

Ventilate the area.

Remove sources of ignition.

8.2. Exposure controls

The use of Personal Protective Equipment (PPE) is not necessary under conditions of normal use.

If handling a leaking or ruptured battery, ensure that the following Personal Protective Equipment (PPE) is used.

Eye/Face Protection

Chemical grade full face shield.

Skin Protection

Acid resistant, natural rubber or neoprene gloves.

Protective rubber apron.

Appropriate Personal Protection with long sleeves and long trousers.

Respiratory Protection

Acid gas filter mask or self-contained breathing apparatus.



Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

Blue cylinder plastic film shell. (a) Appearance:

(b) Odour: Odourless.

(c) Odour threshold; No information available. No information available. (d) pH:

(e) Melting point/freezing point; >300°C

(f) Initial boiling point and boiling range; No information available. No information available. (g) Flash point; (h) Evaporation rate; No information available. No information available. (i) Flammability (solid, gas); (j) Upper/lower flammability or explosive limits; No information available. No information available. (k) Vapour pressure; (I) Vapour density; No information available. (m) Relative density; No information available. (n) Solubility (ies); Partially soluble in water. (o) Partition coefficient: n-octanol/water; No information available. (p) Auto-ignition temperature; No information available. (q) Decomposition temperature; No information available. (r) Viscosity; No information available.

9.2 Other information No information available.

No information available.

No information available.

(s) Explosive properties;

(t) Oxidising properties.



Section 10. Stability and Reactivity.

10.1. Reactivity No information available.

10.2. Chemical stability Stable under normal temperatures and pressures.

10.3. Possibility of hazardous reactions10.4. Conditions to avoidHazardous polymerisation will not occur.Avoid exposure to heat and open flame.

Avoid mechanical or electrical abuse.

Prevent short circuits.

Prevent movement which could lead to short circuits.

Strong oxidizing agents, corrosives.

Metal oxides, CO, CO₂

10.5. Incompatible materials

10.6. Hazardous decomposition products

Section 11. Toxicological Information.

11.1. Information on toxicological effects

Potential health risks:

Eye: Contact with battery contents may cause severe irritation and burns. Eye damage is possible.

Skin: Contact with battery contents may cause severe irritation and burns.

Absorption through the skin will cause localized inflammation.

Ingestion: May cause severe and permanent damage to the digestive tract. May cause circulatory system failure.

Contents of an open battery can cause serious chemical burns to the mouth, oesophagus and gastrointestinal tract.

Section 12. Ecological Information.

When properly used and disposed of correctly, the battery does not present an environmental hazard.

Do not release internal components into water ways, wastewater or ground water.

Section 13. Disposal Considerations.

13.1. Waste treatment methods

Disposal of the battery must be in accordance with local authority regulations.

The battery should be completely discharged prior to disposal and the terminals taped or capped to prevent short circuit.

Do not dispose of batteries with household waste.

Do not dispose of batteries at landfill sites.

Do not incinerate batteries.

UN 3481



Section 14. Transport Information.

14.1. UN number

ADR. International Carriage of Dangerous Goods by Road.

14.2. Name and Description Lithium ion batteries contained in equipment

Label 9

Special Provisions 188 230 348 376 377 360 636

Limited Quantities 0
Excepted Quantities E0

Packing Instructions P903 P908 P909 LP903 LP904

Special Packaging Provisions

14.3. Transport hazard class(es) Class 9

Classification Code M4
Transport Category 2
Tunnel restriction code E

14.4. Packing group P903 P908 P909 LP903 LP904

14.5. Environmental hazards Does not present an environmental hazard.

14.6. Special precautions for user No special precautions necessary.

IATA. International Air Transport Association.

14.1. UN number UN 3481

14.2. UN Proper Shipping Name/Description Lithium ion batteries contained in equipment

Hazard Label. Miscellaneous

Excepted Quantity E0

Packaging Instructions Passenger 967 Section II

Ltd Qty Forbidden
Cargo 967 Section II

ERG Code 9F

Special Provisions A48 A99 A154 A164

A181 A185

14.3. Transport hazard class(es) Class or Division

14.4. Packing group Not applicable to UN 3481

14.5. Environmental hazards Does not present an environmental hazard.

14.6. Special precautions for user No special precautions necessary.

IMDG. International Maritime Dangerous Goods.

14.1. UN number UN 3481

14.2. UN proper shipping name Lithium ion batteries contained in equipment

Special Provisions 188 230 348 360 957

Limited Quantities 0
Excepted Quantities E0
Packaging Instructions P903
Packing Provisions Class or Division 9

Subsidiary Risk(s)

14.4. Packing group

14.3. Transport hazard class(es)

14.5. Environmental hazards Does not present an environmental hazard.

14.6. Special precautions for user No special precautions necessary.

14.7. Transport in bulk – Maritime only. Bulk transport is not applicable to this product



Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture No information available.

15.2. Chemical safety assessment No information available.

Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

H250: Catches fire spontaneously if exposed to air.

H261: In contact with water releases flammable gases.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their

particular purpose.

Issue level	Date	Revisions
1	14/07/16	First issue.

End of Safety Data Sheet.