

### Section 1. Product and Company Identification.

1.1 Model Number; 1.2 Description; TA090 v1 Paint Thickness Gauge Battery: 1.5 Volts. 23 grams.

#### 1.3 Manufacturer;

Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 31 January 2013

### Section 2. Hazards Identification.

Battery is hermetically sealed and does not present a hazard under normal conditions of use.

**Ingestion:** Swallowing a battery can be harmful. Contents of an open battery can cause serious chemical burns of mouth, oesophagus, and gastrointestinal tract.

Inhalation: Contents of an open battery can cause respiratory irritation.

**Skin Contact:** Contents of an open battery can cause skin irritation and/or chemical burns.

Eye Contact: Contents of an open battery can cause severe irritation and chemical burns.



### Section 3. Substances.

			Classification	
3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Weight	Hazard Class & Category Code	Hazard Statements
Zinc	7440-66-6	28.25%	Aquatic Acute 1	H400
	1010 10 0	47.000/	Aquatic Chronic 1	H410
Manganese Dioxide	1313-13-9	17.29%	Acute Tox. 4	H302
			Acute Tox. 4	H332
			STOT RE 2	H373
			Aquatic Chronic 2	H411
Graphite	7782-42-5	5.63%	Skin Irrit. 2	H315
			Eye Irrit. 2	H319
			STOT SE 3	H335
Zinc Chloride	7646-85-7	3.96%	Met. Corr. 1	H290
			Acute Tox. 4	H302
			Skin Corr. 1A	H314
			Eye Dam. 1	H318
			STOT SE 3	H335
			Aquatic Acute 1	H400
			Aquatic Chronic 1	H410
Acetylene Black	74-86-2	3.23%	Flam. Gas 1	H220
			Press. Gas	H280
			STOT SE 3	H336
Ammonium Chloride	12125-02-9	0.29%	Acute Tox. 4	H302
			Skin Irrit. 2	H315
			Eye Irrit. 2	H319
			STOT SE 1	H335
			Muta. 2	H341
Lead	7439-92-1	≤ 0.035%	Acute Tox. 4	H302
			Acute Tox. 4	H332
			Muta. 2	H341
			Carc. 2	H351
			Repr. 1A	H360
			STOT RE 1	H372
			Aquatic Acute 1	H400
			Aquatic Chronic 1	H410



#### Section 3. Substances. Continued.

			6	
Cadmium	7440-43-9	≤ 0.0005%	Carc. 1B	H350
			Muta. 2	H341
			Repr. 2	H361
			Acute Tox. 2	H330
			STOT RE 1	H372
			Aquatic Acute 1	H400
			Aquatic Chronic 1	H410
Mercury	7439-97-6	≤ 0.0002%	Acute Tox. 2	H300
			Skin Sens. 1	H317
			Acute Tox. 2	H330
			Muta. 2	H341
			Repr. 1A	H360
			STOT SE 1	H371
			STOT RE 1	H373
			Aquatic Acute 1	H400

For full text of Phrases and Statements, see Section 16.

### Section 4. First Aid Measures.

Batteries do not pose a risk to eyes or skin under normal circumstances. In the case of contact with internal substances;

**4.1** Description of first aid measures

Inhalation	If breathing difficulties develop, remove the person to fresh air.	
	Loosen close fitting clothing.	
	Ensure that person is warm.	
	Get medical attention.	
Skin Contact	Remove contaminated clothing.	
	Wash affected area(s) with soap and water.	
	Seek medical attention if chemical burn(s) appear or if symptoms resist.	
Eye Contact	Irrigate eyes with water for at least 15 minutes while raising eyelid(s).	
	Get medical attention.	
Ingestion	Do not induce vomiting.	
	Do not give food or drink.	
	Get medical attention.	

**4.2.** Most important symptoms and effects, both acute and delayed No information available.

**4.3.** Indication of any immediate medical attention and special treatment needed No information available.

## Section 5. Fire Fighting Measures.

**5.1.** Extinguishing media Any extinguishing media. Use extinguishing media that is appropriate for the surrounding area.

**5.2.** Special hazards arising from the substance or mixture Move batteries away from a fire incident, if safe to do so. Cool batteries to reduce the risk of rupture.

**5.3.** Advice for fire-fighters

Fire Fighters should wear self-contained breathing apparatus and appropriate Personal Protective Equipment. Thermal degradation may produce hazardous fumes or zinc and manganese; hydrogen gas, caustic vapours of potassium hydroxide and other toxic by-products.

### Section 6. Accidental Release Measures.

**6.1.** Personal precautions, protective equipment and emergency procedures Wear appropriate protective clothing, see Section 8.

**6.2.** Environmental precautions Ventilate area.

**6.3.** Methods and material for containment and cleaning up

Collect in a leak proof container.

Place battery in a sealed bag with an absorbent such as sand, silica, chalk, lime powder or vermiculite. Rinse contamination with water.

Prevent contaminated water from entering sewers or water courses.

6.4. Reference to other sectionsSee Section 7 for information on Safe HandlingSee Section 8 for information of Personal Protective Equipment.See Section 13 for information on disposal.

### Section 7. Handling and Storage.

7.1. Precautions for safe handling

Wear appropriate protective clothing, see Section 8.

7.2. Conditions for safe storage, including any incompatibilities

Store batteries in a well ventilated area.

Do not short circuit a battery. A short circuit causes heating and can lead to ignition of surrounding materials. To minimize the risk of a short circuit, always store batteries in an appropriate container to prevent contact with conductive materials.

Keep batteries away from children.

**7.3.** Specific end use(s)

Intended for use as the battery for the Model Number identified in 1.1 with Description stated in 1.2.





## Section 8. Exposure Controls/Personal Protection.

**8.1.** Control parameters In the event of battery rupture and leakage: Ventilate the area. Remove sources of ignition.

#### 8.2. Exposure controls

The use of Personal Protective Equipment (PPE) is not necessary under conditions of normal use. If handling a leaking or ruptured battery, ensure that the following Personal Protective Equipment (PPE) is used.

**Eye/Face Protection** Chemical grade full face shield.

#### **Skin Protection**

Acid resistant, natural rubber or neoprene gloves. Protective rubber apron. Appropriate Personal Protection with long sleeves and long trousers.

#### **Respiratory Protection**

Acid gas filter mask or self-contained breathing apparatus.

# Section 9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties The following information is not a technical specification or sales specification. Manganese Dioxide: Black powder. (a) Appearance: Acetylene Black: Black powder. Zinc: Silver metal. Zinc Chloride: Colourless liquid. Ammonium Chloride: Colourless liquid. (b) Odour: Zinc Chloride: Stimulative Ammonium Chloride: Stimulative. (c) Odour threshold; No information available. (d) pH: No information available. (e) Melting point/freezing point; Manganese Dioxide: 535°C Zinc: 420°C Zinc Chloride: -2°C Ammonium Chloride: -2°C (f) Initial boiling point and boiling range; Zinc Chloride: 104°C Ammonium Chloride: 104°C (g) Flash point; No information available. No information available. (h) Evaporation rate; No information available. (i) Flammability (solid, gas); (j) Upper/lower flammability or explosive limits; No information available. (k) Vapour pressure; Zinc Chloride: 3mmHg at 20°C Ammonium Chloride: 3mmHg at 20°C No information available. (I) Vapour density; (m) Relative density; No information available. (n) Solubility (ies); Zinc Chloride: Complete. Ammonium Chloride: Complete. (o) Partition coefficient: n-octanol/water; No information available. (p) Auto-ignition temperature; No information available. (q) Decomposition temperature; No information available. (r) Viscosity; No information available. No information available. (s) Explosive properties; (t) Oxidising properties. No information available. 9.2 Other information No information available.

## Section 10. Stability and Reactivity.

10.1. Reactivity
10.2. Chemical stability
<b>10.3.</b> Possibility of hazardous reactions
10.4. Conditions to avoid
10.5. Incompatible materials
<b>10.6.</b> Hazardous decomposition products

No information available. Stable. Hazardous polymerisation will not occur. Do not short circuit, charge or dispose of in fire. No information available. No information available.



## Section 11. Toxicological Information.

11.1. Information on toxicological effects

The materials that comprise this battery are hermetically sealed.

The potential for exposure to materials is negligible when this battery is used as directed. See Section 7.

Inappropriate handling and / or inappropriate use of this battery may result in release of the materials that are sealed within.

Inhalation, skin contact and eye contact are possible when the battery is opened.

Exposure to internal components and corrosive fumes will cause irritation to the eyes, skin and mucous membranes.

### Section 12. Ecological Information.

When properly used and disposed of correctly, the battery does not present an environmental hazard. Do not release internal components into water ways, wastewater or ground water.

<b>12.1.</b> Toxicity	No data available.
<b>12.2.</b> Persistence and degradability	No data available.
<b>12.3.</b> Bioaccumulative potential	No data available.
<b>12.4.</b> Mobility in soil	No data available.
<b>12.5.</b> Results of PBT and vPvB assessment	No data available.
12.6. Other adverse effects	No data available.

### Section 13. Disposal Considerations.

13.1. Waste treatment methods

Disposal of the battery must be in accordance with local authority regulations.

The battery should be completely discharged prior to disposal and the terminals taped or capped to prevent short circuit.

Do not dispose of batteries with household waste.

Do not dispose of batteries at landfill sites.

Do not incinerate batteries.

## Section 14. Transport Information.



<u>ADR. International Carriage of Dangerous Goods by Road.</u> Not subject to ADR.

IATA. International Air Transport Association.

Special Provision A123. Batteries not otherwise listed as Dangerous Goods concerning transport by air, no UN Code refers. Examples of such batteries are (but not restricted to) alkali-manganese, zinc-carbon and nickel cadmium batteries.

Any electrical battery or battery powered device, equipment or vehicle having the potential of a dangerous evolution of heat must be prepared for transport so as to prevent:

(a) a short circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or in the case of equipment, by the disconnection of the battery and protection of exposed terminals); and(b) accidental activation.

The statement "Not restricted, as per Special Provision A123" must be included in the description of the article on the Air Waybill when required.

IMDG. International Maritime Dangerous Goods. Not subject to IMDG.

## Section 15. Regulatory Information.



**15.1.** Safety, health and environmental regulations/legislation specific for the substance or mixture No information available.

**15.2.** Chemical safety assessment No information available.

## Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

The above information is believed to be accurate and represents the best information currently available. No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	31/01/13	First issue.
2	20/01/16	Sections 5, 11, 14 and 15
3	02/08/16	Sections 1.2, 3 5 7 8 and 14

End of Safety Data Sheet.