

AIRSHIELD Mk1

ANSI Z87.1

"A BREATH OF FRESH AIR"

The original air circulating face shield for use with all woodworking applications, especially routing and woodturning.


- Excellent value for money.
- A built in quiet fan keeps a constant flow of filtered air across the face.
- Provides protection from inhalation of harmful dust with a pre-filter and fine dust filter.
- Protects eyes and face against impact from flying debris.
- Filter efficiency 95%.
- Lightweight, quiet and comfortable.
- Rechargeable 4 hour removable Ni-MH battery.
- Polycarbonate flip-up visor.
- 4 hour battery as standard. Upgrade to 8 hour use with a second battery.



AirShield and AirShield Pro were cited as "Our Favorites" in Taunton's 2010 TOOL GUIDE pp. 94-97

Includes:

- 1 x 4 Hour Battery
- 1 x Battery Charger
- 1 x THP2 Fine Filter
- 1 x Pre-Filter
- 1 x Airflow Indicator
- 1 x Clear Visor Overlay
- 1 x Carry Bag



Specification:

Rating	_____	DIY/Craftsman/Professional
Airflow min.	_____	4.94cf/min
Airflow fully charged	_____	6.36cf/min
Size of headband	_____	20-1/2"-24-1/2"
Size range	_____	6-3/4"-7-3/4"
Mean filtered particle size	_____	0.6 micron
Motor sound level	_____	70dB
Battery	_____	4 hrs
Weight	_____	1.6 lbs

Eye protection to ANSI Z87.1 (low energy impact)
Respiratory protection (for reference only) NPF20.
Not NIOSH approved.

Product Reference:

U*AIRSHIELD

Replacement Parts:

Visor Wipes

U*AIR/WIPE (contains 100 wipes)

Replacement THP2 Fine Filter

U*AIR/10 (1 off)

Replacement THP2 Fine Filter Pack

U*AIR/1 (pack of 3)

Replacement Pre-filter

U*AIR/2 (pack of 3)

Replacement Visor Overlay - clear

U*AIR/3C (pack of 10)

Replacement Visor Overlay - green anti-tint

U*AIR/3G (pack of 10)

Replacement 4 Hour Battery

U*AIR/4

Replacement Charger

U*AIR/5L/USA

To extend to 8 hour battery life purchase AIR/4 and AIR/5L/USA.

Woodturners Spare Pack

U*AIR/WSP

Containing: 1x _____ THP-2 Filter
3x _____ Pre-filters
10x _____ Clear Visor Overlays
1x _____ Replacement Face Seal



Face Seal



Flip-up Visor



Routing