




Router not included.



Product Reference:
U*STAIR/A

Includes:

- 1 x Sub-Base
- 1 x Adjustable Reversible Clamp
- 1 x Reversible Clamp Bar
- 1 x Nosepiece
- 1 x Line-up Pin & Bush
- 2 x Spanners
- 1 x 1/2" Shank TCT 3/4" Ø Router Bit



Compatibility
www.trend-usa.com/compatibility



STAIRCASE HOUSING

This template jig is a well proven means of routing out closed riser stair housings quickly and accurately.

- Constructed from hard wearing solid laminate and includes a reversible fence for exact matching of stair strings and fully adjustable nosing piece.
- Built-in heavy duty front clamp for quick clamping for each trench. Unique to Trend jigs.
- Adjustable to suit private and common stair angle pitch.
- TCT dovetail router bit, 3/4" diameter with 1/2" shank for 1-1/8" tread included Ref. U*32/12X1/2TC.
- Standard TCT dovetail bits are offered for various tread thicknesses for closed risers.
- Sub-base is pre-drilled to suit Trend/Dewalt/Elu 1/2" routers.
- All heavy duty routers over 2 HP can be used but sub-base will require re-drilling by user to suit router base configuration.



Specification:

Rise max. _____ 8-1/4"
Tread max. _____ 12"

Optional Accessories


Recommended Dovetail Bits.
To allow other tread sizes to be routed.

	Dia.	For Tread Thickness
U*32/10X1/2TC	9/16"	7/8"
U*32/11X1/2TC	5/8"	1"
U*32/12X1/2TC	3/4"	1-1/8"
U*32/13X1/2TC	7/8"	1-1/4"

SHELF SUPPORT TEMPLATE

A template to allow routing or drilling of 32mm (1-1/4") center holes for 5mm diameter shelf supports.

- Made from clear plastic, with graduation scales.
- Adjustable clamping bar with two locking knobs.
- Can be used with MDF, timber & particle board.
- Some routers may require a Unibase to accept the guide bush.



Product Reference:

U*TEMP/SS/A

Size: 19-11/16" x 5-1/8" x 5/16"

Includes:

- 12 x Plain Metal Shelf Supports
- 1 x Knurled Repeat Index Pin
- 1 x 3/8" Euro Guide Bush



Accessories:

Metal (Glass) Shelf Support

U*SS/M5/12 (pack of 12)
With rubber sleeve for glass.
Sleeve can be removed.
Pin=5mmØ



Brass Plated Shelf Support

U*SS/B5/12 (pack of 12)
Pin=5mmØ
Load capacity 220.5 lbs.



Plastic Shelf Support

U*SS/P5/12 (pack of 12)
Load capacity 220.5 lbs.



Suitable Bit



U*C174X1/4TC
Dia. 5mm x 1-3/8" length

5mm Shelf Support Drill Bit Guide

A quick release shank lip and spur 5mm HSS drill bit guide, which when used with a template will allow 5mm diameter blind holes to be drilled for 5mm Shelf Supports.

U*TEMP/SSD/5MM



Load capacity applies to four shelf supports being evenly distributed.