
Router not included.

CONTRACTOR HINGE JIG with adjustable apertures.



The two piece aluminum Hinge Jig is a portable template set designed for recessing hinges in wooden doors & frames. It is easy to use with minimal setting-up time, completing the job both accurately & quickly.

- Used on-site & in joinery shops to increase productivity with excellent results.
- Four apertures for fire door requirements.
- No need for marking out in the conventional way.
- Quick & simple to set-up as the hinge is used as the pattern.
- Clean & accurate recesses are achieved every time.
- Suitable for timber based doors & square butt hinges.
- Use with a light duty router with 1/4" collet.
- TCT router bit, 15/32" diameter with 1/4" shank included Ref. U*C019AX1/4TC.
- Angled position slots to prevent creep.

Product Reference:

U*H/JIG/A







Н	inge	sizes	possib	ole
---	------	-------	--------	-----

Length min	2-5/8"
Length max.	5"
Width min.	3⁄8"
Width max.	1-3/8"

Door sizes possible

Height min.	6' 5"
Height max.	6' 10"
Thickness min	5/8"

U*H/JIG/8FT and U*H/JIG/A

5/8" Guide Bush

Extra long projection.

Screw-on Style U*GB/US/160

Euro Style U*GB160



Long Reach Bit (15/32" dia.) U*C019AX1/4TC

Carry Case U*CASE/HJ/A

Replacement Parts: Optional Accessory:

Universal Sub-Base

Certain makes & models of router including the T4 will require a Unibase to accept the Euro Style guide bushes.

II*IINIRASE



Includes:

- 4 x Apertures
- 2 x Bradawls
- 1 x 5/8" Screw-in & Euro Style **Guide Bush**
- 1 x T-Handle Hex Key
- 1 x 5/32" Spacing Gauge
- 1 x Fabric Storage Case
- 1/4" Shank TCT 15/32"Ø



HOW IT WORKS:

Setting the Length



Setting the Width



Setting the Depth



Routing Hinge Recesses



Fitting the Door



-| 9"|-