PIVOT FRAME JIG SET

The Pivot Frame Jig Set is universal in nature and performs a number of valuable routing applications.



Specifications:

Beam Trammel:

5/16" dia. x 19-1/2" long rods min/max. 6-5/8" / 33-7/8"

Disc Cutting & Mini Pivot Trammel:

Dia. with long 19-1/2" rods min/max. 25/64" / 12-1/2"

Converts to a beam trammel in seconds.

- Permits surface ski frame operations.
- Anti-tipping device for template routing.
- Cuts rings, scalloped designs & decorative patterns.

Product Reference:

U*PFJ/SET/1

For Trend T3, T4, T5, T5 MK2, Elu MOF 96(E) & DeWalt DW613, 614, 615, 620 & 621.

Includes:

- 2 x End Bars
- 4 x Nylon Shoe Assembly
- 2 x Micro Adjustment Rods
- 1 x Pivot Trammel Point

Optional Accessories:

Long Fence Rods

For Trend T3, T4, T5 & T5 MK2 - 5/16" dia. x 19-1/2"

U*ROD/8X500 (pair)

Packet of 8 Spacers 1/8" thick x 5/16" bore.

II*DI/1



Router not included

treno



Beam Trammel



Ski Frame



Anti-tip Frame

ROUTER T-SQUARE

The Router T-Square can be used as a straight guide for routing housings, squaring & trimming boards and jig setting.



Router and clamp not included.

- Made from hard wearing solid phenolic resin.
- Has false cheek fitting facility.
- Squareness tolerance 1/32" over 39-1/4".
- It is also ideal as a general workshop square for marking and setting out.

Product Reference:

U*RTS/1000

UTER COMPASS For cutting circles & arcs from 4" up to 24" radius. OUTER COMPASS Compatibility www.trend-usa.com/compatibility Made of clear plastic. Printed graduated scale for Router not precise radius setting. included Fits to the base of a router. Includes: **Main Plate Specification:** 'V' Pivot Point Radius min. 1/8" Pivot Point Radius max. 2 x Fixing Screws **Product Reference:** U*R/COMPASS/A