# **PIVOT FRAME JIG SET**

The Pivot Frame Jig Set is universal in nature and performs a number of valuable routing applications.

## **Specifications:**

Beam Trammel: 5/16" dia. x 19-1/2" long rods min/max. 6-5/8" / 33-7/8"

Disc Cutting & Mini Pivot Trammel: Dia. with long 19-1/2" rods min/max. \_\_25/64" / 12-1/2"

#### Optional Accessories: Long Fence Rods For Trend T3, T4, T5 & T5 MK2 - 5/16" dia. x 19-1/2" U\*ROD/8X500 (pair)

Packet of 8 Spacers 1/8" thick x 5/16" bore.



Beam Trammel

Converts to a beam trammel in seconds.

- Permits surface ski frame operations.
- Anti-tipping device for template routing.
- Cuts rings, scalloped designs & decorative patterns.

# Product Reference: U\*PFJ/SET/1

For Trend T3, T4, T5, T5 MK2, Elu MOF 96(E) & DeWalt DW613, 614, 615, 620 & 621.

### **Includes:**

**Ski Frame** 

- 2 x End Bars
- **4 x** Nylon Shoe Assembly
- 2 x Micro Adjustment Rods
- **1 x** Pivot Trammel Point



Compatibility

www.trend-usa.com/compatibility

Anti-tip Frame

# **ROUTER T-SQUARE**

00000

trend

Router not included.

The Router T-Square can be used as a straight guide for routing housings, squaring & trimming boards and jig setting.

Router and clamp not included.

39-1/4" long blade.

Made from hard wearing solid phenolic resin.

- Has false cheek fitting facility.
- Squareness tolerance 1/32" over 39-1/4".

It is also ideal as a general workshop square for marking and setting out.

Product Reference: U\*RTS/1000





www.trend-usa.com

20

Ne