NEW VARIJIG FRAME SYSTEM **Adjustable frame & quide** for use with a router. Adjustable frame for rectangles and squares. Allows a router to cut recesses, slots, face panel moulds etc. Four lengths of 27-1/2" extrusion with dual metric/imperial measuring scales. Working area 23-1/2" x 23-1/2". Cross cut accuracy to 5 thou, a square is required to square frame before use. Use with a guide bush with minimum 5/16" spigot length, or use Unibase as guide. Router not included Can also be used to create panel doors for kitchens etc. Includes: **Replacement Parts: 4 x** Alloy Extrusions with Scales **Frame Jointing Kit 4 x** Corner Brackets Set of four corner jointing brackets. 1 x Anti-tilt Shoe U*VJS/FJK **1 x** Anti-tilt Shoe Fixing Screw Compatibility **Optional Accessories:** www.trend-usa.com/compatibility **Product Reference: Clamp Kits** VARIJIG II*VIS/CK

Pair of sliding friction clamps with 1-1/4" clamping thickness. **Recommended Guide Bush 1-3/16"**

Euro Style with extra long 3/8" spigot.

U*GB30/A

Screw-on Style. U*GB/US/30

Universal Sub-base

U*UNIBASE

Certain makes & models of router will require a Unibase to accept the Euro Style guide bush Ref. U*GB30/A.

VARIJIG TENON & GROOVING JIG


Allows grooves & tenons to be cut using a router.

- Can be used to crosscut boards with a router or circular saw.
- Frame is adjustable to allow narrower or wider grooves to be routed. The max. adjustment is 2-3/4" depending on the diameter of the router base.
- The edge of the frame can be used as a guide to trim a panel square using a router.
- Two sliding stops to set groove length.
- Squaring butt has the facility to accept a spelch block to allow a full-length groove. Fixing screws are included for this purpose.
- Working length is 15-3/4".
- Use with a router with a guide bush with a minimum 3/8" projection fitted.

Product Reference: U*VJS/TG/JIG







Squares



Anti-tilt Shoe

Router and

clamps

not included.

trend

G Includes: 4 x Alloy Extrusions 4 x Corner Brackets 3 x Scales 1 x Squaring Butt 2 x Length Stops

1 x Hex Key

Rectangles

Optional Accessories: F Clamps

U*FC/200

Quick action (two required). Recommended Guide Bush 1-3/16"

Euro Style with extra long 3/8" spigot.

Screw-on Style.



Trimming



Crosscutting

.

Compatibility www.trend-usa.com/compatibility



Trenching/Grooving