

GUIDE BUSH READY CHART

Euro Style Guide Bush

Will fit directly to certain European plunge type routers including Trend and smaller Dewalt machines. To fit the guide bush to other makes and models, a universal sub base Ref. U*UNIBASE or circular sub-base Ref. U*GB/5 can be used. The U*UNIBASE is designed to suit the most popular plunge type routers. The GB/5 can be re-drilled by the user. The U*GB/5/M is designed for Porter Cable routers.



Screw-on Style Guide Bush



Will fit directly to a number of routers using the 1-3/16" diameter thread and knurled nut. The sub-base Ref. U*GB/5/US has been designed to allow the Screw-on Style guide bush to be used with routers which do not have the fitting as standard. The U*GB/5/US can be re-drilled by the user.

KEY

- Euro Style guide bush.
- Screw-on Style guide bush.
- Not applicable.
- U Unibase recommended (See p.24).
- ✓ The product will fit the router.
- X The product will not fit router.

PRODUCT REF.	PAGE	ROUTER COLLET Ø	GUIDE BUSH STYLE & DIA. INC. WITH PRODUCT	GUIDE BUSHES AVAILABLE AS ACCESSORY	TREND T4 ROUTER
U*T4EK 1/4" 1.1HP Router	8	1/4"	5/8" Euro & Screw-on Style Adapter Plate	or various sizes see page 25	-
U*PRT Professional Router Table	12	-	-	-	X
U*CDJ300/600 Craft Dovetail Jig(s)	13	1/4"	5/8" Ø	various sizes included with accessory templates	✓
U*MT/JIG Mortise & Tenon Jig	14	-	7 sizes	1-5/16", 1-1/16", 15/16" in set U*GB/US/D	✓
U*RBT Routabout Hole Cutter Jig	15	1/4"	Plastic 1-3/16" Ø	Steel 1-3/16" Ø	✓
U*STAIR/A Staircase Housing Jig	16	1/2"	-	-	X
U*TEMP/SS/A Shelf Support Template	16	1/4"	3/8" Ø	-	✓
U*COMB166 Kitchen Countertop Worktop Jig	17	1/2"	1-3/16" Ø	1-3/16" Ø	X
U*H/JIG/A Hinge Jig	18	1/4"	5/8" Ø	-	U
U*LOCK/JIG Lock Jig	19	1/2"	1-3/16" Ø	or 5/8" Ø 1-3/16" Ø	Faceplate only
U*RTS/1000 Router T-square	20	-	-	-	✓
U*R/COMPASS/A Router Compass	20	-	-	-	✓
U*PFJ/SET/1 Pivot Frame Jig Set	20	-	-	-	✓
U*ME/JIG Mini Ellipse Jig	21	-	-	-	✓
U*ELLIPSE/J/A Ellipse Jig	21	-	-	-	✓
U*VARIJIG Variable Frame System	22	-	not included	or 1-3/16" Ø	✓
U*VJS/TG/JIG Varijig Tenon & Grooving	22	-	not included	or 1-3/16" Ø	✓
U*TEMP/LN57 For Number & Letter Templates	23	-	Plastic 1/2" Ø	-	U
U*INLAY/KIT/A Inlay Kit for Inlay Templates	23	1/4"	5/16" Ø	-	U
U*UNIBASE Universal Sub-base	24	-	Plastic 5/8" Ø	various sizes see page 25	✓
U*TEMP/TRK Timber Repair Kit Template	24	1/4"	20mm Ø	-	U
U*GB/5 Sub-base for Euro Style guide bushes	25	-	5/8" Ø	various sizes see page 25	✓
U*GB/5/US Sub-base for Screw-on Style guide bushes	25	-	-	various sizes see page 25	-

CONVERSION CHART

Inches	mm
1/32	0.5
1/16	1.5
3/32	2
1/8	2.5
5/16	3
3/8	3.5
7/16	4
1/2	4.5
9/16	5
5/8	5.5
11/16	6
3/4	6.5
7/8	7
1	7.5
1 1/16	8
1 1/8	8.5
1 1/4	9
1 1/2	9.5
1 3/4	10
2	10.5
2 1/16	11
2 1/8	11.5
2 1/4	12
2 1/2	12.5
2 3/4	13
3	13.5
3 1/16	14
3 1/8	14.5
3 1/4	15
3 1/2	15.5
3 3/4	16
4	16.5
4 1/16	17
4 1/8	17.5
4 1/4	18
4 1/2	18.5
4 3/4	19
5	19.5
5 1/16	20
5 1/8	20.5
5 1/4	21
5 1/2	21.5
5 3/4	22
6	22.5
6 1/16	23
6 1/8	23.5
6 1/4	24
6 1/2	24.5
6 3/4	25
7	25.5
7 1/16	26
7 1/8	26.5
7 1/4	27
7 1/2	27.5
7 3/4	28
8	28.5
8 1/16	29
8 1/8	29.5
8 1/4	30
8 1/2	30.5
8 3/4	31
9	31.5
9 1/16	32
9 1/8	32.5
9 1/4	33
9 1/2	33.5
9 3/4	34
10	34.5
10 1/16	35
10 1/8	35.5
10 1/4	36
10 1/2	36.5

COPYRIGHT

© 2008 Trend Routing Technology Inc. All rights reserved. No part of this publication may be reproduced or transmitted without prior permission. Trend Routing Technology Inc. cannot be held liable for any material rendered unusable, or for any form of consequential loss. The descriptions specifications and other claims made with respect to the products featured in this brochure are made as of the date of printing. Trend Routing Technology Inc. retains the right to discontinue production of or make improvements or other changes to any of its products without notice. Product packaging and other product literature should be consulted for current descriptions specifications and other claims relating to Trend Routing Technology Inc. products. Improvements or other changes to products shall not obligate Trend Routing Technology Inc. to make corresponding improvements or changes to products previously manufactured or sold. All Trademarks Acknowledged.

GUARANTEE TREND LIMITED TOOLING WARRANTY

All Trend tools are engineered and manufactured to the highest standards for optimum performance and service life. Trend warrants to the original purchaser at retail that each new Trend tool shall be free from defects in material and workmanship, subject to the guidelines below. Upon verification of failure or malfunction, Trend shall, at its option, within (28) days, repair or replace the tool. Subject to the guidelines below.

Guidelines

- In the event of failure or malfunction, return the product, properly packaged and postage prepaid, to Trend Routing Technology Inc.
- All implied warranties for Trend's power tools (INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE) are limited to the period of one year from the purchase date. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.
- A warranty claim shall be limited to repair or replacement as stated in Trend's Limited Tool Warranty and in no event shall Trend be liable for any other direct, indirect or consequential damages, costs or expenses. INCIDENTAL AND CONSEQUENTIAL DAMAGES ARE EXCLUDED UNDER ALL WARRANTIES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above may not apply to you.
- Trend warranties give you specific legal rights, and you may also have other rights, which vary from state to state.
- Trend warranties shall not be deemed to have failed their essential purpose while Trend is willing to repair or replace defective products.
- Trend assumes no liability for defects or damage caused by abuse or misuse of any product or unauthorized service of any product. The product must have been used for its recommended purpose and not modified by sharpening or other changes. Normal wear and tear are not covered under Trend warranties.
- Any action for breach of warranty must be commenced within one year after the accrual of the cause of action.