

# STAIRCASE HOUSING

This template jig is a well proven means of routing out closed riser stair housings quickly and accurately.



Router not included.




- Constructed from hard wearing solid laminate and includes a reversible fence for exact matching of stair strings and fully adjustable nosing piece.
- Built-in heavy duty front clamp for quick clamping for each trench. Unique to Trend jigs.
- Adjustable to suit private and common stair angle pitch.
- TCT dovetail router bit, 3/4" diameter with 1/2" shank for 1-1/8" tread included Ref. U\*32/12X1/2TC.
- Standard TCT dovetail bits are offered for various tread thicknesses for closed risers.
- Sub-base is pre-drilled to suit Trend/Dewalt/Elu 1/2" routers.
- All heavy duty routers over 2 HP can be used but sub-base will require re-drilling by user to suit router base configuration.



**Compatibility**  
www.trend-usa.com/compatibility



**Product Reference:**  
**U\*STAIR/A**



## Includes:

- 1 x Sub-Base
- 1 x Adjustable Reversible Clamp
- 1 x Reversible Clamp Bar
- 1 x Nosepiece
- 1 x Line-up Pin & Bush
- 2 x Spanners
- 1 x 1/2" Shank TCT 3/4" Ø Router Bit



## Optional Accessories

### Recommended Dovetail Bits.

To allow other tread sizes to be routed.

	Dia.	For Tread Thickness
<b>U*32/10X1/2TC</b>	9/16"	7/8"
<b>U*32/11X1/2TC</b>	5/8"	1"
<b>U*32/12X1/2TC</b>	3/4"	1-1/8"
<b>U*32/13X1/2TC</b>	7/8"	1-1/4"

## Specification:

Rise max. \_\_\_\_\_ 8-1/4"  
Tread max. \_\_\_\_\_ 12"

# SHELF SUPPORT TEMPLATE

A template to allow routing or drilling of 32mm (1-1/4") center holes for 5mm diameter shelf supports.

Product Reference:

**U\*TEMP/SS/A**

Size: 19-11/16" x 5-1/8" x 5/16"

- Made from clear plastic, with graduation scales.
- Adjustable clamping bar with two locking knobs.
- Can be used with MDF, timber & particle board.
- Some routers may require a Unibase to accept the guide bush.

## Includes:

- 12 x Plain Metal Shelf Supports
- 1 x Knurled Repeat Index Pin
- 1 x 3/8" Euro Guide Bush



Router not included.

## Accessories:

### Metal (Glass) Shelf Support

**U\*SS/M5/12** (pack of 12)  
With rubber sleeve for glass.  
Sleeve can be removed.  
Pin=5mmØ



### Brass Plated Shelf Support

**U\*SS/B5/12** (pack of 12)  
Pin=5mmØ  
Load capacity 220.5 lbs.



### Plastic Shelf Support

**U\*SS/P5/12** (pack of 12)  
Load capacity 220.5 lbs.



### Suitable Bit



**U\*C174X1/4TC**  
Dia. 5mm x 1-3/8" length

### 5mm Shelf Support Drill Bit Guide

A quick release shank lip and spur 5mm HSS drill bit guide, which when used with a template will allow 5mm diameter blind holes to be drilled for 5mm Shelf Supports.

**U\*TEMP/SSD/5MM**

