

8 FOOT HINGE JIG

Patent No. GB2285410

with adjustable apertures.

A three part phenolic plastic Hinge Jig for 8 foot doors, supplied in a fabric carry case.

- Door size minimum 7' 11" (95") and maximum 8' (96").
- Three part phenolic jig with alloy jointing plates.
- Hinge positions for 8 foot door can be set at 4-7/8" down, 30-3/8" down, 55-7/8" down and 81-3/8" down.
- Door width maximum 2".
- Suits hinges between 2-3/4" to 5-1/2" long.
- Supplied with four bradawls, 1/4" shank router bit and template guide bush.

Product Reference:

U*H/JIG/8FT



Router not included.



Compatibility

www.trend-usa.com/compatibility

Specification:

Hinge sizes possible

Length min. _____ 2-3/4"
 Length max. _____ 5-1/2"
 Width min. _____ 3/8"
 Width max.** _____ 1-3/8"


Door sizes possible

Height min. _____ 7' 11"
 Height max. _____ 8' 0"
 Thickness min. _____ 5/8"
 Thickness max. _____ 2"

** A wide hinge can be accommodated if a 1/2" overhang offset is used.

Hinge recess corners have a 15/64" radius, which will need to be squared off with a corner chisel. Ref. U*C/CHISEL.

Example of hinge position on 7' 11" door using 4-1/2" hinges.



Includes:

- 1 x 1/4" Shank Router Bit
- 4 x Bradawls
- 1 x 5/8" Guide Bush
- 1 x T-Handle Hex Key
- 1 x Fabric Storage Case



HOW IT WORKS:

Setting the Length



Setting the Width



Setting the Depth



Routing Hinge Recesses



Fitting the Door

