

VARIJIG 100" STRAIGHT GUIDE

For guiding routers, circular saws and jigsaws.

- Two lengths of extrusion with jointing piece to give maximum working length of 100" (2540mm). Reduced length for easier transport and storage.
- Clamps can slide along each extrusion.
- Maximum material clamping thickness 1-1/4".
- Adjustable friction washer on clamps prevent clamp from sliding too freely.
- One extrusion has dual metric/imperial scale.
- Can be combined with Varijig parts.

Product Reference:

U*VJS/G/100

Includes:

- 1 x 56" Alloy Extrusion with Scale
- 1 x 56" Alloy Extrusion
- 1 x Connecting Block
- 1 x Hex Key 4mm (5/32")
- 2 x 1-1/4" Sliding Friction Clamps



Saw not included.



Crosscutting



Router, saw and clamps not included.

VARIJIG 36" ANGLE GUIDE

For the router or circular saw.

- Adjustable angle guide to allow grooving with a router, or crosscutting with a circular saw.
- Adjustable angle range from 25° to 155°.
- Preset angle for 30°, 45°, 60°, 90°, 120°, 135° and 150°.
- Router working length at 90° is 36" (915mm). Circular saw working length at 90° is 30-3/4" (780mm).
- Angle tolerance ± 0.2° with zeroing facility.
- Adjustable position alloy extrusion with scale.
- Requires three clamps.

Includes:

- 1 x Extrusion with Scale
- 1 x Protractor Plate
- 1 x Locking Pin
- 1 x Hex Key



Crosscutting

Product Reference:

U*VJS/AG/36

VARIJIG EXTRA LONG PIVOT CLAMPS

Pair of pivoting sliding friction clamps with 2" clamping thickness.

- 360 degree clamp rotates to allow the pad of the clamp to be secured firmly to the work-piece.
- The clamp can be used with the Varijig system including the varijig set, straight guides and angle guide.
- Aluminum body with soft pads to prevent marring of component.
- Friction lock design, so they can be positioned in extrusion without sliding out end when clamp lifted up.

Product Reference:

U*VJS/PCK/L



Optional Accessories for Varijig System:

Clamp Kits (Fit to extrusions on Varijig System)

Pair of sliding friction clamps with 1-1/4" clamping thickness.

U*VJS/CK

Pair of long sliding friction clamps with 2" clamping thickness.

U*VJS/CK/L

Connecting Block Kit

Jointing block for extrusions.

Can be used to join Varijig extrusions together.

U*VJS/G/CB

Recommended 1-3/16" Guide Bush

Euro Style with extra long 3/8" spigot for U*VJS/TG/JIG or U*VARIJIG.

U*GB30/A

Screw-on Style.

U*GB/US/30

Universal Sub-base

Certain makes & models of router will require a Unibase to accept the Euro Style guide bush Ref. U*GB30/A.

U*UNIBASE

