
VARIJIG CLAMP GUIDES

VARIJIG CLAMP GUIDES

Self clamping, straight line clamp guides that use the Varijig low profile extrusion.



 Low profile extrusion with integral clamping of work-piece, double locking mechanism and two full length T-slots.

Common Varijig extrusion to 24 inch (610mm), 36 inch (915mm) and 50 inch (1270mm) Clamp Guides.

■ Metric and imperial sliding scale.

Extrusion profile 5/8 inch (16mm) high x 2-1/8 inch (54mm) wide.

Ref. U*VJS/CG/PRO8 is an extra wide clamp 5 inch (127mm) with four T slots. Ideal for large sheet material. Clamps up to 96 inch (2.44 metre).

Jaws have fixing holes for accessories.

Product Reference	Length
U*VJS/CG/24	24" / 610mm
U*VJS/CG/36	36" / 915mm
U*VJS/CG/50	50" / 1270mm
U*VJS/CG/PRO8	8' / 96" / 2440mm







ACCESSORIES

A range of accessories for use with Varijig Clamp Guides

ROUTER BASE PLATE NEW

Plunge router base accessory.

- Base plate engages in the T-slot in the extrusion.
- Made from clear plastic.
- Includes adjustable guide bar for perfect tracking using hex key provided.



U*VJS/CG/RBP

Router, bit & clamp guide not included.



Base plate engages in the T-slot in the extrusion.

 Includes adjustable guide bar for perfect tracking using hex key provided.

Product Reference:

U*VJS/CG/SBF

Saw & clamp guide not included.



END STOP BLOCK

Adjustable end stop block.

Engages in the T-slot on the clamp guide extrusion and can be locked in position using locking knob.

Product Reference:

U*VJS/CG/ESB

Clamp guide not included.



HANDLE EXTENSION

Lever extension handle for Varijig clamp guides

- Gives better leverage to operate the clamp, especially when more clamping pressure is required.
- Increases lever length by 5-1/4 inch (134mm).
- Can be fitted and removed quickly.

Product Reference:

U*VJS/CG/EXT

Clamp guide not included.



