




SHANK MOUNTED BEARING RADIUS


- Single blade.
- Bearing allows groove to be routed to the template.
- Template thickness should be 10mm thicker than cut length.



R mm	D mm	C mm	B mm	Product Ref.	Shank Dia. 1/4"
6.3	12.7	13.0	12.7	RT/100	£40.48 +

BEARING GUIDED RADIUS



- Two blades.
- Replaceable tips are ideal for prolonged use on man-made materials.
- Low profile bearing fixing screw.



R mm	D mm	C mm	B mm	Product Ref.	Shank Dia. 1/4"
6.3	25.0	12.7	12.7	RT/260	£45.32 +

BEARING GUIDED ROUND OVER


- Two blades.
- Replaceable tips increase productivity.
- Low profile bearing fixing screw.



R mm	D mm	C mm	B mm	Product Ref.	Shank Dia. 1/4"
6.3	26.0	15.7	12.7	RT/130	£52.99

BEARING GUIDED OGEE


- Two blades.
- Replaceable tips allow dimensions to be constant.
- Low profile bearing fixing screw.



R mm	D mm	C mm	B mm	Product Ref.	Shank Dia. 1/4"
4.5	26.0	15.7	12.7	RT/65	£45.32 +

REPLACEABLE BLADES FOR ROTA-TIP CUTTERS

Product Ref.	L mm	W mm	T mm	46/01	46/02	46/03	46/010	RT/04, 05, 06, *10, *11(M), 21 & TR43	RT/07, 08, 15	RT/12(M) & 14	RT/13	RT/23	RT/30, 31 & 32	RT/33	RT/39	RT/41	RT/50, 51 & 60	RT/65	RT/70	RT/72, 75	RT/80	RT/81	RT/100	RT/130	RT/260	RT/325RH	RT/329LH	RT/331	RT/343	RT/391	Each	Pack of 10		
STRAIGHT BLADE																																		
RB/A	29.5	9.0	1.5				•																									£7.67	£67.49	
RB/B	49.5	12.0	1.5								•																					£9.14	£77.80	
RB/C	29.5	12.0	1.5							•																						£6.36	£53.60	
RB/D	7.5	12.0	1.5																													£8.35	£75.04	
RB/E	12.0	12.0	1.5	•		•							•	•	•		•															£4.89	£37.57	
RB/F*	30.0	12.0	1.5																													£6.36	£50.00	
RB/G	8.4	5.6	1.1	•																												£3.58	£28.58	
RB/H	49.5	9.0	1.5																													£9.14	£75.04	
RB/I	20.0	9.0	1.5				•																									£7.67	-	
RB/J	29.5	9.0	1.5																													£7.67	-	
RB/L	13.2	9.0	1.5																													£5.96	+	
RB/T	50.0	12.0	1.7																														£11.41	£97.48
SHAPED BLADE																																		
RB/M	12.0	9.0	1.5																													£5.96	+	
RB/N	12.0	12.0	1.5																													£7.67	-	
RB/O	15.7	9.0	1.5																													£5.96	-	
RB/P	15.7	9.0	1.5																													£7.67	-	
RB/Q	13.5	9.0	1.5																													£5.96	+	
RB/R	28.0	9.0	1.5																													£9.14	-	
RB/R/LH	28.0	9.0	1.5																													£9.14	-	
RB/S	16.3	12.3	2.0																													£20.25	-	



* Blade Ref. RB/F does not have bevelled ends for clearance.

Packs of 10 blades are supplied in protective sliding plastic boxes. Please add suffix /10 for ten pack reference.



ROTA-TIP REPLACEABLE TIPS

Blades are fitted directly onto the tool body without removing the cutter from the router, reducing downtime to a minimum. When replacing blades, please ensure they are placed into the correct seating of the tool body. Ensure the body or slot is free of debris and/or burrs, as this may cause fracture of the blade. Do not over-tighten fixing screws. Run test cuts prior to production to ensure blades are aligned correctly.