







80mm plunge



VARIABLE SPEED WORKSHOP ROUTER

With built-in Quick Raiser fine height adjuster. Same features as T10 opposite but also has:

- Router fine height adjuster for above and below height adjustment. One revolution of handle equals 1.5mm.
- Three quick release recesses in base to fit tables in conjunction with optional Quick Release Kit.
- Fitting for optional Clamp Guide System Kit.
- Extra large base aperture for large cutters.
- Quick release dust spout.







Standard guide bush fitting.

Inner plate centring for superior accuracy.

75mm aperture for large cutters in table mode.

With 90mm recess to house panel raisers.



Built-in Quick Raiser for table fine height adjustment



Enables quick fitting and removal of router to PRT, router tables and jigs when used with optional Quick Release Kit. EC Design Reg. No. 000336763.

75mm aperture for large cutter in table mode.

trend

Clamp guide fitting to suit VJS clamp guides

INCLUDES: 1 x 1/2" Collet 1 x Fine height adjuster 1 x Guide bush 30mm with inner plate and line-up pin 1 x Clip-in dust spout 35mm 1 x Side-fence with micro 1 x Storage case

SPECIFICATION	l :	
Rating		Professional / Trade
Plunge stroke		0-80mm
Power input		2000w
Standard collet dia		1/2"
No load speeds		8-20000 rpm
Dust spout size (ID)	35mm
Guide bush dia. supplied		30mm
Cutter dia. max. plunge/table		70/86mm
Other collet dia.	3mm, 6mn	n, 1/4", 8mm, 3/8", 10mm and 12mm
Weight		6.3kg
Voltages		230v or 115v*

*All 115v routers over 1850W require a 32A BS4343 115v plug.Minimum generator or transformer requirement 3 kVA continuous with a 32A BS4343 115v socket outlet. 115v units cannot be used on the no-volt release switch CRT/MK3L and PRT/L router tables.

T11 ACCESSORIES:		Price
Comprising: three sets of cams, bolts & fixings		
Varijig clamp guide system kits Comprising: alloy bracket fixing & plastic slider. Allows T11 to join to Varijig Clamp Guides.		£46.58
	WP-T11/087	£68.16
50mm 70mm	GB500 + GB700 +	£15.56 £15.56
5 volt plug	PLUG/110V/32A	£43.10
	s A plastic slider. np Guides. 50mm 70mm	s S S S S S S S S S

