

PRO ROUTER TABLE

Professional portable router table with aluminium surface and backfence for floor and bench mounting use.

- Backfence squareness adjustment for absolute accuracy.
- T11E quick release fixing holes for fitting T11 fixing kit.
- Bench leg level adjustment when mounted on a bench.
- 20mm hole for the T11 Quick Raiser adjuster handle.
- Floor or bench standing with removable legs and adjustment for uneven floors.
- Extruded 8mm thick aluminium alloy table top with minimal loss of cutter depth.
- Cutter aperture of 90mm allows the use of the largest router cutters available.
- Cast backfence with extruded adjustable alloy cheeks and 'T' slots.
- Made to EN standards, with backfence accuracy of 0.5° and table flatness of 0.5mm.
- Suitable size and weight enabling easy re-positioning around the workshop and transportation for on-site use.

PRT (240v) £613.20 or
PRT/L (115v) £613.20

4 Insert rings
In sizes 20mm, 35mm, 54mm and 72mmØ, to suit different cutter diameters.



Soft rubber feet to prevent movement.



Bench leg level adjustment
For uneven surfaces.



Flip-up finger pressure and guard assembly
For easy access to cutter.



T11 quick release fixing holes
Allows T11 to be fitted to the table quickly and removed when used with optional Quick Release Kit.



Mitre fence
Mitre fence with zeroing and splch block facility.



Quick raiser
Includes hole for T11's fine height adjuster.

INCLUDES:

4 x Insert rings
1 x No-volt release switch
1 x Mitre fence
2 x Finger pressures
1 x Large adjustable safety guard
1 x Lead-on pin
1 x Pushstick


SPECIFICATION:

Rating	Professional / Trade
Table size	650mm x 550mm
Bench height	350mm
Height with legs	860mm
Router cutter aperture	90mmØ
Insert ring sizes	20mm, 35mm, 54mm, 72mmØ
Backfence height	110mm
Dust spout aperture	57mmØ (2-1/4")
Voltage	240v or 115v
Weight	26.2kg

115v unit supplied with 16A BS4343 plug and socket.
Not intended for continuous production or production line use.

Fits the following routers directly:

TREND T5, T5 MK2, T9, T10♦, T11♦ BOSCH GOF1600A, 1700ACE CMT CMT1E, 2E
DEWALT DW613, 614, 615, 620, 621, 624, 625E♦ 626♦, 629♦ DRAPER PT1200V
ELU MOF96(E) MK2, 131, 177(E), OF97(E) MAKITA RP0910, 1110C PERLES OF808(E) >1999 ♦ Not 115v



Guard assembly
Quick lateral and height adjustment of finger pressure and guard.



Backfence
Quick release 110mm cast aluminium backfence with adjustable aluminium cheeks and squareness adjustment.



57mmØ (2-1/4") dust spout aperture
With freehand lead-on pin park.



90mmØ aperture
For larger panel raiser cutters.

Side scales to set backfence.

Pushstick park on rear.

No-volt release switch with 115 volt (16A) available.

Leg clamps to remove lower legs and adjust for uneven floors.

Side finger pressures
Adjustable position for different widths of timber.

OPTIONAL ACCESSORIES:	Product Ref.	Price
1. T11 quick release kit Allows T11 router to be quickly fitted and removed from table.	T11/JT/KIT	£30.56
2. Hose with adaptor 39mmØ x 3 metre with 57mmØ (2-1/4") adaptor fitted.	CRT/4	£25.02



⚠ 115v routers over 1850w (including T10 and T11) cannot be used with no-volt release switch router tables. Removable centre plate of table will need to be re-drilled for other makes and models of medium and heavy duty routers.

To download videos, test reviews, spare parts & instruction manuals visit: www.trend-uk.com/downloads

Router & cutters not included.