## **MORTISE & TENON JIG**

International PCT application No. PCT/GB02/00253

## Enables mortise and tenons and dowel joints to be cut with a router. Ideal for cabinet, chair and table construction.

- · CNC precision manufactured plates and body.
- One set-up for both mortise and tenon giving perfectly fitting joints.
- Fully adjustable for compound angle joints up to 45°.
- Reversible templates to produce round and square . end tenons.
- Templates can be used for accurate dowelling applications.
- Cuts mortise and tenon sizes of 1/4" (6.3mm) to 5/8" (15.9mm).
- Guide bushes are included but cutters are required. •
- A Unibase may be required for certain makes and • models of router.
- Tenons are cut with a 5/8" (15.9mm) diameter • straight cutter (Ref. C026). The width of the tenon is adjusted by using different guide bush diameters.

**MT/JIG** £236.58 MT/JIG/EURO\* £236.58

\* Metric size jig requires metric cutter set Ref. SET/MT2X8MMTC. This set comprises 6, 8, 10, 12 and 16mm dia. straights. Shank dia 8mm





12mm

Routing the mortise

## Setting-up square tenon SPECIFICATION:

Material thickness min.



Tenon thickness min.   4.8mm     Tenon thickness max.   16mm     Tenon width max. using   90mm     vertical guide +   90mm     Tenon length max. ++   25mm     Mortise length max. using   vertical guide +++     90mm   -10° to 45°     + on end of 100mm wide material.   ++     ++ depending on cut length & plunge depth of router.	Material thickness max.	4/mm	
Tenon width max. using     vertical guide +   90mm     Tenon length max. ++   25mm     Mortise length max. using   vertical guide +++   90mm     Angle tilt compound   -10° to 45°     + on end of 100mm wide material.   ++ depending on cut length & plunge depth of router.	Tenon thickness min.	4.8mm	
vertical guide + 90mm   Tenon length max. ++ 25mm   Mortise length max. using vertical guide +++ 90mm   Angle tilt compound -10° to 45°   + on end of 100mm wide material.   ++ depending on cut length & plunge depth of router.	Tenon thickness max.	16mm	
Tenon length max. ++ 25mm   Mortise length max. using vertical guide +++ 90mm   Angle tilt compound -10° to 45°   + on end of 100mm wide material.   ++ depending on cut length & plunge depth of router.	Tenon width max. using		
Mortise length max. using vertical guide +++ 90mm Angle tilt compound -10° to 45° + on end of 100mm wide material. ++ depending on cut length & plunge depth of router.	vertical guide +	90mm	
vertical guide +++ 90mm Angle tilt compound -10° to 45° + on end of 100mm wide material. ++ depending on cut length & plunge depth of router.	Tenon length max. ++	25mm	
Angle tilt compound     -10° to 45°       + on end of 100mm wide material.       ++ depending on cut length & plunge depth of router.	Mortise length max. using		
+ on end of 100mm wide material. ++ depending on cut length & plunge depth of router.	vertical guide +++	90mm	
++ depending on cut length & plunge depth of router.	Angle tilt compound	-10° to 45°	
	++ depending on cut length & plunge		

+++ unlimited if vertical guide removed and wood repositioned.

## RECOMMENDED





Router cutters

1/4" shank

8mm shank

1/2" shank

Tenon width

1/4" (6.3mm)

5/16" (7.9mm)

8mm shanks for metric jigs

Double loose tenon

OPTIONAL ACCESSORIES: Product Ref.

COMPATIBILITY

www.trend-uk.com/compatibility

trend-uk.com/video

VIDEO

то WATCH

SET/MT1X1/4TC SET/MT1X8MMTC

SET/MT1X1/2TC

SET/MT2X8MMTC

Dowel joints

trend

Side angled tenon

Price 2. Steel guide bushes (optional) A set of 5 long reach straight cutters with diameters of 1/4" to **GB15** 5/8" suitable for use with the Mortise & Tenon Jig.

£66 03

£66.03

£67.49

£66.03

Guide bush dia.

1-1/4" (31.8mm)

1-3/16" (30.2mm)


- GB222, GB238, GB27, GB286, GB302, GB318 & GB333 (ea) £9.14 Universal sub-base Certain makes and models of router will require a Unibase to accept the guide bushes.
- UNIBASE £20.51 Dust kit
- Magnetic fitting dust kit with 57mmØ (2-1/4") dust spout aperture and 35mm ID adaptor. Accepts 39mm OD hose

MT/DUSTKIT £36.58

trend

153

£10.08




Cutter Ref.

C008

C012

3/16" (4.8mm)	C003	1-5/16" (33.3mm)
7/16" (11.1mm)	C018	1-1/16" (27mm)
9/16" (14.3mm)	C024	15/16" (23.8mm)





Router not included.