## CONTRACTOR TWO PART SKELETON HINGE JIG Made from aluminium extrusion for strength and light weight for

easy transport. To recess hinges in wooden doors and frames. Clean and accurate recesses are achieved every time with minimal set-up time, both on-site and in joinery shops.

- · Fully adjustable guick release aperture blocks.
- Adjustable edge guides with three preset hinge widths.
- Suitable for timber based doors and square butt hinges. • No need for marking out in conventional way.
- Use with a light duty router with 1/4" collet and long reach router cutter 12mm dia. x 70mm overall length.
- Jig thickness allows it to be used on frames with . a maximum 25mm thick fixed stop fitted.
- Can be used to fit new door in an old frame. Ideal for renovation work.

## **H/JIG/C** (two piece) £267.35



- With fully adjustable quick release apertures.
- Fully adjustable hinge recesses. Can be used on max. 25mm thick
- fixed stops.
- Also suitable for fire doors.
- Adjustable stops plus three preset stop positions for 20mm, 25mm & 30mm hinge leaf.



Adjustable stops plus three preset stop positions for 20mm, 25mm & 30mm hinge leaf.



Large pivot plate



COMPATIBILITY www.trend-uk.com/compatibility

trend-uk.com/video

2mm guide bush offset built in making hinge length setting easier.

## SKELETON

INCLUDES: 3 x Aperture block assemblies 4 x Bradawls (short blade) 1 x 16mmØ guide bush 1 x Fabric storage case

## SPECIFICATION:

Weight	2.9kg
Hinge sizes possible	
Length min.	2-5/8" (67mm)
Length max.	5" (127mm)
Width min.	1/2" (12.7mm)
Width max.	1-3/8" (35mm)
Door sizes possible	
Height min.	6' 5" (1956mm)
Height max.	6' 10" (2100mm)*
Thickness min.	5/8" (16mm)
Thickness max.	2" (51mm)
* Please note for doors over 2040mm the bottom hinge will be higher than 9" up.	

Price

£20.51

£30.30

£11.92

F

E ORO trend





1981mm

Router & cutter not included

Patent No. GB2490139

bush.

**ROUTING JIGS**