
## 36" **VARIJIG VARIABLE ANGLE GUIDE**

#### Adjustable angle guide to allow grooving with a router, or crosscutting with a circular saw.

- Preset angle locations for 30°, 45°, 60°, 90°, 120°, 135° and 150°.
- Router working length at 90° is 915mm (36"). Circular saw working length at 90° is 780mm (30").
- Angle tolerance ± 0.2° with zeroing facility.
- · Adjustable position alloy extrusion with scale.
- Requires three clamps or a pair of accessory Varijig friction clamps Ref. VJS/CK, VJS/CK/L or VJS/PCK/L.

### VJS/AG/36 £62.37



Preset angles





ACCESSORY DIRECT FIT CLAMPS:	Product Ref.	Price
1. Clamp kit (pair)	VJS/CK	£24.83
Sliding friction clamps with 32mm clamping th	ickness.	
2. Long clamp kit (pair)	VJS/CK/L	£37.54
Sliding friction clamps with 51mm (2") clamping thickness.		
3. Long pivot clamp kit (pair)	VJS/PCK/L	£23.60
Sliding friction clamps with 51mm (2") clampir pivots to allow guide to be set at an angle.	ng thickness. Cla	mp head





# SELF CENTRING **MORTISE BASE**

#### Allows a plunge router to rout mortises in the centre of timber quickly.

- Self centres up to 100mm wide material.
- 30mm long rolling nylon guides for greater support and smoother • operation.
- Creates round ended mortises.
- Made from heavy duty plastic and includes 1/4" shank centre • line-up bush.
- Base holes drilled for TBC configuration.
- Maximum cutter diameter 16mm. •
- · Can be used with a pencil to mark centre.

### **TEMP/SCM/A** £38.25



INCLUDES: 1 x Circular base plate 1 x Line-up pin & plug 1 x Pencil plug



nd

## **OFFSET BASE**

This teardrop shaped base is fitted to the router to allow better control when edge moulding by preventing router tilt.

- Large grip knob for greater control.
- Pre-drilled for Trend, Elu and DeWalt routers.
- Can be re-drilled by user to suit other makes of router.
- Made from clear plastic.
- **OFS/BASE** £30.15

Size: 280 x 180 x 8mm









INCLUDES: 1 x Teardrop shaped base 1 x Knob assembly 2 x Fixing screws

# OFFSET TRENCHING BASE

Ideal for housing cuts where oversize or undersize board is used.

- Allows wider grooves to be routed by simply rotating the base.
- Pre-drilled for Trend, Elu and most DeWalt routers.
- Can be re-drilled by user to suit other makes of router.
- The distance from the centre hole to the shortest edge is 100mm, subsequent edge distances are 101mm, 102mm, 103mm, 104mm and 105mm.
- Made from clear plastic.

### **TEMP/OTB/A** £30.15

Size: 200 x 200 x 8mm, offset: 1mm, 2mm, 3mm, 4mm & 5mm





#### INCLUDES:


1 x Hexagon shaped base 1 x Dual 1/4", 8mm line-up taper pin 2 x Fixing screws

 REPLACEMENT PART:
 Product Ref.
 Price

 Spare taper pin
 TEMP/OTB/PIN1
 £7.88

OFFSET





# **ROUTER T-SQUARE**

The router t-square can be used as a straight guide for routing housings, squaring and trimming boards and jig setting.

- 1000mm long blade.
- Blade has two parallel edges to allow router to run on both sides.
- It is also ideal as a general workshop square for marking and setting out.
- Made from hard wearing solid phenolic laminate.
- Butt has two M5 tapped holes for fitting of a false fence.
- Squareness tolerance 0.5mm over 1 metre.
- Squareness adjustment facility.

RTS/1000 £60.43



