

# BUTT HINGE TEMPLATE

A routing template that allows a router to create a hinge recess on a door.

- Made from clear 8mm thick plastic.
- Includes metal templates for 75mm and 100mm butt hinges.
- Magnets in template frame to hold templates.
- Cuts rounded corners which can be removed with a corner chisel or chisel.
- Use on doors from 35mm to 44mm thick.
- Requires 12mm diameter cutter and 30mm guide bush.
- User-made batten 44mm x 34mm x 450mm and two F-clamps are required.

**TEMP/BH/A** £46.58

Size: 214 x 135 x 8mm



**COMPATIBILITY**  
www.trend-uk.com/compatibility



[trend-uk.com/video](http://trend-uk.com/video)

**OPTIONAL ACCESSORIES:**

	Product Ref.	Price
<b>Recommended 1/4" shank cutters</b>		
Professional 12mmØ router cutter	<b>3/8LX1/4TC</b>	£30.30
CraftPro 12mmØ router cutter	<b>C019AX1/4TC</b>	£20.25
<b>Recommended 30mm guide bush</b>		
(A Unibase may be required)	<b>GB30</b>	£9.14
<b>Extra templates</b>		
3" template	<b>WP-BH/T/3</b>	£9.14
4" template	<b>WP-BH/T/4</b>	£9.14

**INCLUDES:**

- 1 x 75mm Template
- 1 x 100mm Template

# LOCK RECESS TEMPLATE

Clear plastic template for use with any plunge router to accurately fit 2, 3 and 5 lever sash and dead mortise locks.

- Clear plastic with magnets to hold metal templates.
- Includes six faceplate recess and three mortise templates.
- Requires 12mm diameter x 63mm cut length cutter with 1/2" shank and 30mm guide bush. A 1/4" shank extra long cutter can also be used but deepening of mortise with auger bit will be required.
- User-made batten 44mm x 34mm x 450mm and two F-clamps are required.

**TEMP/LR/A** £61.92

Size: 320 x 135 x 8mm



**COMPATIBILITY**  
www.trend-uk.com/compatibility

**TEMPLATES INCLUDED:**

Faceplate Dimensions:		
Imperial	Metric	Template
7/8" x 6-1/8"	22.2 x 156mm	1
7/8" x 6"	22.5 x 152.5mm	2
1" x 5-1/4"	25.4 x 133.5mm	5
1" x 6"	25.4 x 153mm	7
1" x 6-3/8"	25.6 x 162mm	12
-	25.1 x 57mm	15

Mortise Dimensions:		
Imperial	Metric	Template
5/8" x 4-1/4"	16 x 107mm*	B
3/4" x 3"	19 x 79mm*	C
5/8" x 3-17/32"	16 x 90mm*	E

\* These are maximum mortise lock case (body) lengths, unless radius ends are squared with a chisel. Actual length of mortise is 7mm longer. Smaller mortise locks can be accommodated depending on position of their fixing screws.

**OPTIONAL ACCESSORIES:**

	Product Ref.	Price
<b>Recommended 1/2" shank cutters</b>		
Professional 12mmØ router cutter	<b>3/75X1/2TC</b>	£45.25
CraftPro 12mmØ router cutter	<b>C172X1/2TC</b>	£25.79
63mm cut length.		
<b>Recommended 1/4" shank cutters</b>		
Professional 12mmØ router cutter	<b>3/8LX1/4TC</b>	£30.30
CraftPro 12mmØ router cutter	<b>C019AX1/4TC</b>	£20.25
70mm overall length. Deepening of mortise with auger bit required.		
<b>Recommended 30mm guide bush</b>		
(A Unibase may be required)	<b>GB30</b>	£9.14

**SUITABLE FOR FOLLOWING LOCKS:**

Additions H32306, H32331, Chubb 3U75, 3G114, ERA 196-62, 201-31, 201-32, 202-32, 208-31, 221-31, 301-32T, 302-32T, 467-32T, 471-32T, 571-32T, latch, ES bed latch, Jewson LISJK072, LISJK100, Legge P3751, P1645, Travis Perkins P19, P20, P22 (802503), P29 (802510), P81, Union L99, Y2201, Y2294, Yale PM246, PM320 and PM550.