STANDARD POCKE

For fast and accurate joining of timber and plywood giving strong instant joints.

- Solid hardened bushes, with variable pitch of 29mm to 63mm.
- Use on timber, MDF, plywood and blockboard.
- · Allows a variety of joints to be created individually.
- · Uses square drive self tapping screws.
- Workpiece can be handled immediately after gluing and screwing creating time saving benefits.
- No clamps required.

PH/JIG £71.44





1. Adjust column position.



2. Clamp timber



Drill pocket hole sockets.



Drive self tapping screws to secure.

APPLICATIONS FOR BOTH JIGS:







INCLUDES:

100 x Dome head screws 1 x Face clamp 1 x HSS drill bit with collar 1 x 75mm Square drive bit 1 x 150mm Square drive bit 3 x Hex key



SPECIFICATION:

| Material thickness min. | 16mm |
|-------------------------|-------------|
| Material thickness max. | 38mm |
| Material width min. | 38mm |
| Hole pitch | 29mm-63mm |
| Drill diameter | 9.5mm |
| Square drive bit size | No.2 |
| Screw size | No.7 x 30mm |

| REPLACEMENT PARTS: | Product Ref. | Price | |
|--------------------------------|--------------|--------|--|
| Stepped drill bit 9.5mm (3/8") | PH/DRILL/95 | £15.63 | |
| 2. Drill collar 9.5mm (3/8") | PH/COLL/95 | £3.86 | |
| 3. No.2 square drive bit 75mm | SNAP/SQ/2A | £5.82 | |
| 4. No.2 square drive bit 150mm | SNAP/SQ/2B | £7.02 | |
| 5. Face clamp 150mm (6") | PH/CLAMP/F6 | £10.90 | |





Short base for repair work.


MINI

For fast and accurate joining of timber and plywood giving strong instant joints.

- Supplied with two bases, long base with stop for standard pocket hole jointing or short base for repair work of an assembled component.
- The flush short base also allows screws to be centred on the material thickness.
- Adjustable pitch centres from 18mm to 54mm.
- Use on timber, MDF, plywood and blockboard.
- Workpiece can be handled immediately after gluing.
- · Compact size ideal for use on site.

PH/JIG/M £37.99





Long base with stop for standard joints.

Short base for repair work.



1.
Adjust column position.



Set collar height.




3. Clamp to timber and drill pocket hole sockets.



Drive self tapping screws to secure.



Edge to edge joints.



OPTIONAL ACCESSORIES FOR BOTH JIGS:

Square drive self tapping screws



| INICI | HDEC. |
|--------|--------|
| IIIVCL | .UDES: |

| 1 x | Long base |
|------|---------------------------|
| 1 x | Short base |
| 50 x | Dome head screws |
| 1 x | HSS drill bit with collar |
| 1 x | 150mm Square drive bit |
| 2 x | Hex key |



SPECIFICATION:

| Material thickness min. | 16mm |
|-------------------------|--------------|
| Material thickness max. | 38mm |
| Material width min. | 38mm |
| Hole pitch | 18mm-54mm |
| Drill diameter | 9.5mm |
| Square drive bit size | No.2 |
| Screw sizes | No. 7 x 30mm |

| Material thickness max. | 38mm | |
|-------------------------|--------------|--|
| Material width min. | 38mm | |
| Hole pitch | 18mm-54mm | |
| Drill diameter | 9.5mm | |
| Square drive bit size | No.2 | |
| Screw sizes | No. 7 x 30mm | |
| | | |

| 1. | No.7 x 30mm dome head standard (pack of 500) | PH/7X30/500 | £11.18 |
|----|--|---------------|--------|
| 2. | No.7 x 30mm dome head coarse (pack of 500) ldeal for softer woods, plywood and particle board as | DITENSO (2000 | 045.05 |
| | thread gives better holding power. | PH/7X30/500C | £15.25 |
| 3. | Quick release shank 3/8" drill bit A 9.5mm diameter stepped High Speed Steel drill. Supplied with depth setting collar. | PH/DRILL/95Q | £15.99 |
| 4. | 3/8" Pocket hole plug cutter Tool steel plug/pellet cutter with 8mm shank. Use in a pillar drill to allow 9.5mm plugs to be made to cover the pocket hole pockets. Allows plugs up to 52mm long to be created in end grain. | PH/PC/95 | £21.68 |

Product Ref.

Price







