

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture
Product name : Trendicote, PTFE Dry Lubricant
Product code : TRENDICOTE, TRENDICOTE/60, PTFE Dry Lubricant
Type of product : Aerosol
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Industrial/Professional use spec : Industrial cutting tool dry lubricant
For professional use only

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Trend Machinery & Cutting Tools Ltd
Unit 6 Odhams Trading Estate
St. Albans Road
Watford
Herts
United Kingdom
T 0044 1923 249911
F 0044 1923 236879
technical@trendm.co.uk
www.trend-uk.com

1.4. Emergency telephone number

Emergency number : 0044 7973629367 Wessex Chemical Factors

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aerosol 1 H222;H229
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT SE 3 H336

Full text of H-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

GHS04

Signal word (CLP) :

: Danger

Hazardous ingredients

: acetone, propan-2-one, propanone

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
: H229 - Pressurized container: may burst if heated.
: H315 - Causes skin irritation.
: H319 - Causes serious eye irritation.
: H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
: P102 - Keep out of reach of children.
: P103 - Read label before use.
: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
: P251 - Do not pierce or burn, even after use.
: P261 - Avoid breathing vapours, mist, spray.
: P264 - Wash hands thoroughly after handling.

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015

- : P271 - Use only outdoors or in a well-ventilated area.
- : P280 - Wear eye protection, protective gloves.
- : P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
- : P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- : P312 - Call a POISON CENTER or doctor/physician/if you feel unwell.
- : P332 + P313 - If skin irritation occurs: Get medical advice/attention.
- : P337 + P313 - If eye irritation persists: Get medical advice/attention.
- : P362 + P364 - Take off contaminated clothing and wash it before reuse.
- : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
- : P405 - Store locked up.
- : P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
- : P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone, propan-2-one, propanone	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8	>=30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	1 - 20	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If breathing is difficult, trained personnel should give oxygen. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : If the person is fully conscious, make him/her drink warm water (1/2 litre). Never give an unconscious person anything to drink. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015

Symptoms/injuries after inhalation : Nausea, vomiting. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard : May form flammable/explosive vapour-air mixture.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****6.1.1. For non-emergency personnel**

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist /vapours/spray

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Flush contaminated areas with plenty of water. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour. Avoid breathing vapours. Use only outdoors or in a well-ventilated area.

Handling temperature : ≤ 50 °C

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from: Direct sunlight. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : ≤50 °C

7.3. Specific end use(s)

No additional information available

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acetone, propan-2-one, propanone (67-64-1)

United Kingdom	WEL TWA (mg/m ³)	1210 mg/m ³ 8 hours
United Kingdom	WEL TWA (ppm)	500 ppm 8 hours
United Kingdom	WEL STEL (mg/m ³)	3620 mg/m ³ 15 minutes
United Kingdom	WEL STEL (ppm)	1500 ppm 15 minutes

xylene (1330-20-7)

United Kingdom	WEL TWA (mg/m ³)	220 mg/m ³ 8 hours
United Kingdom	WEL TWA (ppm)	50 ppm 8 hours
United Kingdom	WEL STEL (mg/m ³)	441 mg/m ³ 15 minutes
United Kingdom	WEL STEL (ppm)	100 ppm 15 minutes

No additional information available

8.2. Exposure controls

Personal protective equipment:

: Avoid all unnecessary exposure. Gloves. Protective goggles. Protective clothing.

Hand protection

: Wear protective gloves.

Eye protection

: Chemical goggles or safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.



Other information

: Do not eat, drink or smoke during use

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: White.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: - 29 °C
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Open flame. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Oxidizing materials. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

acetone, propan-2-one, propanone (67-64-1)

LD50 oral rat	5800 mg/kg
---------------	------------

xylene (1330-20-7)

LD50 oral rat	5251 mg/kg
LD50 dermal rabbit	> 4200 mg/kg 4 hour exposure; up to 5 ml per dose
LC50 inhalation rat (Vapours - mg/l/4h)	29091 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
	Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
	Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
	Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
	Based on available data, the classification criteria are not met
Specific target organ toxicity (repeated exposure)	: Not classified
	Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified
	Based on available data, the classification criteria are not met

PTFE Dry Lubricant

Vaporizer	Aerosol
-----------	---------

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

acetone, propan-2-one, propanone (67-64-1)

LC50 fishes 1	5540 mg/l 96 hours (Trout)
---------------	----------------------------

xylene (1330-20-7)

LC50 fishes 1	2,6 mg/l 96 hours (Rainbow trout)
EC50 Daphnia 1	3,82 mg/l 48 hours

12.2. Persistence and degradability

PTFE Dry Lubricant

Persistence and degradability	Contains non readily biodegradable component(s).
-------------------------------	--

xylene (1330-20-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015

PTFE Dry Lubricant

Bioaccumulative potential	No bioaccumulation.
---------------------------	---------------------

xylene (1330-20-7)

Bioconcentration factor (BCF REACH)	< 25,9
Log Kow	3,12 - 3,2
Bioaccumulative potential	Low.

12.4. Mobility in soil

xylene (1330-20-7)

Surface tension	28,47 mN/m
Log Koc	2,73

12.5. Results of PBT and vPvB assessment

Component

xylene (1330-20-7)	PBT: not relevant – no registration required
--------------------	--

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA

14.1. UN number

UN-No. (ADR) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable
Transport document description (ADR) : UN 1950 AEROSOLS , 2.1, (D)
Transport document description (IMDG) : UN 1950 AEROSOLS , 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Hazard labels (ADR) : 2.1
:



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015**IATA**

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing groupPacking group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable**14.5. Environmental hazards**Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available.**14.6. Special precautions for user****14.6.1. Overland transport**Classification code (ADR) : 5F
Special provision (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1L
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207, LP02
Special packing provisions (ADR) : PP87, RR6, L2
Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading and unloading (ADR) : CV9, CV12
Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D**14.6.2. Transport by sea**Special provision (IMDG) : 63, 190, 277, 327, 344, 959
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P207, LP02
Packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and segregation (IMDG) : Protected from sources of heat?

For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but 'Separated from' class 1 except division 1.4.?

For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2.?

For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.

14.6.3. Air transport**14.6.4. Inland waterway transport**

Not subjected to ADN : No

14.6.5. Rail transport

Carriage prohibited (RID) : No

Date of issue: 03/01/2017

Revision date: 03/01/2017

Replaces version 5.0 Version: 6.0
dated: 28/5/2015

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

SECTION 15 : Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions.
PTFE Dry Lubricant is not on the REACH Candidate List.
Contains no REACH candidate substance.
Contains no REACH Annex XIV substances.

15.1.2. National regulations

Germany

Water hazard class (WGK) : 2 - hazardous to water.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

User notes : Sections revised 2, 3, 16
Revision due to change in regulations

Data sources : Regulation (EC) No. 1272/2008 Classification. This mixture has been classified using methods as described in Article 9(4) of Regulations (EC) No.1272/2008.

Other information : Suppliers own data sheet (Wessex Chemical Factors), issued 13/10/2014, revision date 27/02/2015, version 1.1

Trend SDS reference : LEAF/HS/TCOTE

Full text of H- and EUH-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aerosol 1	Aerosol, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurized container: may burst if heated
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.