

FFP2 FACE MASK WITHOUT VALVE PACK OF 20

MODEL NO: 2005/20

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY

- Ensure that all components are in good order and fit for purpose. DO NOT use if you are unsure.
- The mask is for single use only, and should not be removed from its packaging until it is required for use.
- ✓ Wear the mask for the whole period of exposure. It should not be used for more than 8 hours (1 shift) and should be discarded safely and appropriately after use.
- WARNING! The user should be instructed on how to fit the mask properly and made aware of these instructions before using the mask.
- **WARNING!** Use only in adequately ventilated areas which **DO NOT** have a deficiency of oxygen.
- WARNING! Facial hair or beards and certain facial characteristics may reduce the effectiveness of the mask.
- **WARNING!** If the mask is removed whilst in the contaminated area it should be replaced.
- □ WARNING! If the mask is damaged in use it must be replaced.
- **x DO NOT** use the mask in an explosive environment.
- **DO NOT** store or transport masks in direct sunlight. Store in frost free, dry conditions.
 - NOTE: If the User exhibits an allergic reaction to the mask, they must leave the hazard area and seek medical advice.

2. INTRODUCTION

Pack of 20 cup masks class FFP2 NR. Protects against mild toxic or irritant solid and liquid aerosols. Aerosols are defined as a suspension of fine solid particles or liquid droplets in air or another gas. Fitted with adjustable band, nose liner and aluminium nose clip to fit all face contours. Filter efficiency \geq 94%. Manufactured to BS EN 149:2001 + A1:2009.

3. SPECIFICATION

Model No:	
Brand:	Worksafe
Quantity:	

4. FITTING INSTRUCTIONS

- 4.1. Cup mask in one hand with nose piece at fingertips, allow the headbands to hang freely below the hand (fig.1.1)
- **4.2.** Hold mask under chin with nose piece upwards (fig.1.2)
- 4.3. Locate the upper strap across the crown of the head and the lower below the ears, straps must not be twisted (fig.1.2/3/4).
- **4.4.** Using both hands, mould the nose clip to the lower part of the nose to ensure a close fit and good seal. Pinching the nose clip using only one hand may result in less effective performance (fig.1.5).
- 4.5. The mask seal on the face should be fit checked before entering the workplace (fig.1.6).
- **4.6.** If the user feels that the straps are too loose and not possible to achieve a satisfactory seal, the straps may be knotted to shorten them.



Dust mask grade	FFP1	FFP2	FFP3
Protection:	Non-toxic dust and/or water based aerosols**. Minor dust level.	Mild toxic or irritant, solid & liquid aerosols**. Moderate dust level.	Toxic liquids, solids & liquid aerosols**. High dust level.
Application:	Handling rubble, sweeping, drilling concrete.	Plastering, sanding rust & soft wood, grinding & cutting metal, paint spraying (excluding 2-pack isocyanate)*	Paint stripping, sanding of hardwood or cement, copper, chrome or arsenic, welding*.
Substance:	Flour, chalk, graphite, cotton, concrete.	Untreated softwood, coal, powder pesticide, fibreglass.	Biological, pharmaceutical, chrome, lime, lead, asbestos (non-handling).
Filter efficiency:	≥80%	≥94%	≥99%

* The application guide is given as an indication only. Before commencing with any task, please consult with qualified safety personnel, or carry out your own risk assessment, to ensure that the face mask type and rating offers adequate protection for your intended use. You may need to use this mask in conjunction with other safety equipment. These are particulate filters only, and do not provide protection from harmful fumes or gases.

** An aerosol is a suspension of fine solid particles or liquid droplets in air or another gas.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR 01284 757500 01284 703534 @ sales@sealey.co.uk @ www.sealey.co.uk