

HI-VIS YELLOW JACKET WITH QUILTED LINING & ELASTICATED WAIST

MODEL NO: **802L 802LO 802XL 802XLO 802XXL 802XXLO**



Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.



REFER TO INSTRUCTIONS

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.


1. INTRODUCTION

Waterproof motorway jacket with full quilted lining for greater warmth and comfort. Fitted with retractable hood, two outer pockets, inner phone pocket and both zipper and snap closing for added protection against rain.

Conforms to EN ISO 2047:2013+A1:2016 Class 3 and EN 343:2003+A1:2007 Class 3.

2. SIZING

| Size | Chest 'A' cm | Height 'B' cm | |
|---------|--------------|---------------|--|
| Large | 116 - 124 | 170 - 176 | |
| XLarge | 124 - 132 | 176 - 182 | |
| XXLarge | 132 - 140 | 182 - 188 | |



EN ISO 20471:2013+A1:2016 Class 3 Refer to Section 3

EN 343:2003+A1:2007 Class 3:3 Refer to Section 3

EN 343:2003+A1:2007 Class 3:3 Refer to Section 3

3. CLASSIFICATION

| Standard | Attribute | Grade | Definition |
|-----------------------------------|--|---------|---|
| EN ISO 20471:2013+A1:2016 Class 3 | Area of visible material | Class 3 | Highest level of visibility |
| EN 343:2003+A1:2007 Class 3:1 | Water penetration resistance | Class 3 | Highest level of waterproofness |
| | Water vapour resistance (breathability) | Class 3 | The highest level of waterproofness and breathability |

4. SAFETY

- ✓ Always wear the garment fastened.
- ✓ Keep clean should the high visibility properties of this garment become irretrievably soiled, replace if damaged.
- ✓ Dispose of garment in accordance according to local environment guidelines.
- WARNING! Please take care when wearing this garment near moving machinery.

5. CLEANING

- □ WARNING! Maximum 25 cycles of machine washing and follow the care label.
- DO NOT wash in biological powder and use the synthetic cycle on your washing machine.
- ✓ Select a warm and minimum wash, or hand wash.
- \checkmark Cold rinse with a short spin. **DO NOT** Wring out the waistcoat.
- ✓ The stated maximum number of cleaning cycles is not the only factor related to the lifetime of the garment. The lifetime will also depend on the usage, care and storage etc.

6. STORAGE

- ✓ Always store in clean and dry conditions.
- DO NOT store in places subject to direct strong sunlight.

7. OBSOLESCENCE

The period of obsolescence is 1 year from date of purchase. After this, the product should be replaced.





This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at www.sealey.co.uk.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. **Important**: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

EU | Sealey EU Ltd, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland UK | Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR 01284 757500 sales@sealey.co.uk www.sealey.co.uk