

TYPE 5/6 DISPOSABLE COVERALL -LARGE / EXTRA LARGE

MODEL NO:9602L / 9602XL

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



See Specification Section for Labelling

Refer to instruction manual

1. SAFETY

- □ WARNING: Suitable for single-use only. DO NOT re-use.
- □ WARNING: A properly selected coverall is essential to protect your health. Before commencing any task, please consult with qualified safety personnel to ensure that the coverall type and rating offers adequate protection for your intended use.
- □ WARNING: For use only by trained and qualified personnel.
- **WARNING:** Restrictions on the coverall disposal depend solely on the contamination occurring during use.
- ✓ When using the coverall with other PPE and in order to comply fully with EN requirement for Type5/6 garments, all openings such as wrist, ankles, neck etc., should be securely taped.
- The user shall be the sole judge of the suitability for the type of protection required and the correct combinations of coveralls accessories and ancillary equipment.
- ✓ Upon contamination, wear or damage, the coverall should be removed and appropriately disposed of at the earliest opportunity.
- The wearer should always ensure to check the integrity of the coverall before wearing it.
- The possibility of heat stress should be considered in very warm conditions. Heat stress can be reduced or eliminated by the appropriate use of undergarments and ventilation equipment.
- ✓ Extreme of heat and cold may adversely affect the performance of this garment.
- The coverall should not be used where there is a risk to certain hazardous chemicals that have not been tested against. Although limited protection can be offered from various chemicals, please refer to the physical performance of the coverall in relation to Type 5 and 6 testing.
- The user must also wear compatible chemical resistant gloves, boots and respiratory protection. The gloves should cover the elastic cuffs. An appropriate size should be selected by the user to allow for unrestricted movement for the intended task.
- ✓ If necessary please contact Manufacturer/Distributor for advice.
- ✓ It is recommended that the product be used within a period of 3 years from the date of manufacture/production written on the packaging.

2. INTRODUCTION

Microporous film makes the coverall breathable, ensuring comfort during periods of extended use. Elasticated wrists, ankles, hood and waist section. 65gsm Microporous film.

3. SPECIFICATION

Fabric Physical Properties		Class
Abrasion Resistance	EN 530 Meth.2	Class 1
Flex Cracking Resistance	ISO 7854 B	Class 4
Trapezoidal Tear Resist. MD	ISO 9073·4	Class 2
XD		Class 2
Puncture resistance	EN863	Class 1
Tensile Strength MD	ISO 13934-1	Class 1
XD		Class 1
Radioactive Protection	EN1073-2:2002	Class 2
Infective Resistance(solid particles}	ISO 22612	Class 3
Resistance to ignition	EN 13274-4	Pass
Fabric Chemical Properties Test Method	Penetration	Repellency
Resistance to chemical EN 368		
Sulphuric acid 30%	Class 3	Class 3
Sodium Hydroxide 10%	Class 3	Class 3

Protective Clothing Catergory III $\downarrow K \\ C \\ O \\ O \\ O \\ O \\ S \\ S \\ S \\ S \\ S \\ S$	Model No. 9602L Made in China Xianning Huakin Garment Co., Ltd. TYPE 5/6 DISPOSABLE COVERALL - LARGE HXCR-04				
EN1073-2/02 Class 1 SIZE: REG.EU 2016/425 EN1149-5/18 EN14126:2003 100-102 EN150 EN14126:2003 100-102 EN150 EN14126:2003 100-102 EN150 EN14126:2003 100-102 EN150 EN15	路 C € 0338 2895	TYPE5-B ENISO13982-1/04	TYPEG-B ENT3034/05		
	EN1073-2/02				
	SIZE:		176-182 EN ISO		
Batch No:	DOI	NOT REL			

o-Xylene	Class 3	Class 3
Butance-1-ol	Class 3	Class 3
Whole Suit Test Performance		
Type 5 Inward leakage	IL 82/90 ≤30% &TILS 8/10≤15%	
Method as defined by EN ISO 13982-1:2004	Pass	
Type 6 Light spray		
Method as defined by EN 13034:1005	Pass	
En 14126:1003		
Barrier to infective agents	Pass	
En 1073-2:002		
Barrier to radioactive particulates	Pass	
EN 1149-5:2018 Anti-static	Pass	
Protection against Infective Agents EN14126		
ISO 16603	CLASS 6	
ISO 16604	CLASS 6	
EN ISO 22610	CLASS 6	
ISO 22611	CLASS 6	
ISO 22612	CLASS 6	



Approvals:

Shirley®,Notified Body2895 Port Tunnel Business Park,Office 13 Unit 21, Dublin 17, ROI, Ireland. BTTG®,notified body 0338, Unit 6 Wheel Forge Way, Trafford Park, Manchester,M17 EH, United Kingdom.

4. STORAGE

The coverall can be stored in accordance with normal storage practices in a dry environment away from sources of heat, light and direct sunlight.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR 01284 757500 @@_______ sales@sealey.co.uk @______ www.sealey.co.uk