



# OIL HOSE END GUN

MODEL NO: AK4564D.V2

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

**IMPORTANT:** PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instruction manual



Wear protective gloves



Wear eye protection



Wear protective clothing

## 1. SAFETY

- WARNING!** Ensure health & safety, local authority, and general workshop practice regulations are strictly adhered to when using this equipment.
- ✓ Familiarise yourself with product application and limitations, as well as the specific potential hazards peculiar to this product.
- ✓ Maintain the pump station in good condition (use an authorised service agent).
- ✓ Replace or repair damaged parts. *Use genuine parts only. Non authorised parts will invalidate the warranty.*
- ✓ Use only to dispense lubricants up to SAE 150 viscosity.
- ✓ Ensure safety eye protection and protective clothing are worn when using this product.
- ✓ Keep the work area clean, uncluttered and ensure there is adequate lighting.
- ✓ Maintain correct balance and footing. Ensure the floor is not slippery and wear non slip shoes.
- ✓ Keep children and unauthorised persons away from the working area.
- ✓ After use, drain any fluids from the equipment before storage.
- ✓ Dispose of waste liquids in accordance with local authority regulations.
- ✓ Disconnect air pressure from equipment when not in use.
- \* **DO NOT** exceed the maximum working pressure of 1500psi.
- \* **DO NOT** point the nozzle at people or animals.
- \* **DO NOT** use the equipment near open flames.
- \* **DO NOT** smoke whilst using this equipment.
- \* **DO NOT** use to extract corrosive fluids.
- \* **DO NOT** dismantle, tamper with or adapt the gun for any purpose other than for which it is designed.
- \* **DO NOT** use the unit if it has been dropped or mishandled, check the unit to ensure there is no damage.
- ✓ Keep the gun and nozzle clean and store in a safe dry, childproof location.
- WARNING! DO NOT** allow uncontrolled discharge of fluids thus polluting the environment. All liquids must be disposed of according to local authority regulations.

## 2. INTRODUCTION

Robust oil dispensing gun incorporating manual shut off. Fitted with rigid extension, handle lock and non-drip nozzle. Please note that this gun is not approved for resale of oil.

## 3. SPECIFICATION

Model no .....AK4564D.V2  
 Max. flow rate..... 35L/min  
 Inlet size..... 1/2" BSP  
 Max. output pressure .....1500psi

## 4. ASSEMBLY

- 4.1. Attach the nozzle assembly to the gun.
- 4.2. Insert the filter into the inlet connection and then attach the supply hose.  
**NOTE: DO NOT** over tighten the inlet swivel connection or damage may result.



## 5. OPERATION

- 5.1. Open the nozzle valve (fig.1).
- 5.2. Press trigger to dispense liquid, the trigger can be locked open for long periods of dispensing using the clip.
  - **WARNING! DO NOT** leave the gun dispensing unattended.
- 5.3. Release the trigger to stop dispensing.
- 5.4. Close the nozzle valve.




fig.1



### ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

**Note:** It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on [technical@sealey.co.uk](mailto:technical@sealey.co.uk) or 01284 757505.

**Important:** No Liability is accepted for incorrect use of this product.

**Warranty:** Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



01284 703534



[sales@sealey.co.uk](mailto:sales@sealey.co.uk)



[www.sealey.co.uk](http://www.sealey.co.uk)