



# INSTRUCTIONS FOR: GRAVITY FEED/AIR DISCHARGE OIL DRAINER

Model No: **AK458DX.V2**

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



**IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.**

## 1. SAFETY INSTRUCTIONS

### 1.1. GENERAL SAFETY

- **WARNING!** Ensure Health & Safety, local authority, and general workshop practice regulations are adhered to when using this equipment.
- ✓ Familiarise yourself with the application and limitations of the oil drainer, as well as the potential hazards.
- **WARNING!** Disconnect the drainer from the air supply before changing accessories, servicing or performing any maintenance.
- ✓ Maintain the drainer in good condition (use an authorised service agent).
- ✓ Replace or repair damaged parts. Use genuine parts only. Unauthorised parts may be dangerous and will invalidate the warranty.
- ✓ Keep the work area clean, uncluttered and ensure there is adequate lighting.
- ✓ Keep the drainer clean for best and safest performance.
- ✓ Maintain correct balance and footing. Ensure the floor is not slippery and wear non-slip shoes.
- ✓ Keep children and unauthorised persons away from the working area.
- **WARNING!** ensure correct air pressure is maintained and not exceeded.
- ✓ Keep air hose away from heat, oil and sharp edges. Check air hose for wear before each use, and ensure that all connections are secure.
- x **DO NOT** use the drainer for any purpose other than that for which it is designed.
- x **DO NOT** operate the drainer if any parts are damaged or missing as this may cause failure and/or personal injury.
- x **DO NOT** stand on the drainer.
- x **DO NOT** adjust or tamper with the safety valve.
- x **DO NOT** move the drainer by the hose, or yank the hose from the air supply.
- x **DO NOT** place attachments close to your face (especially eyes, ears, etc.) and do not point hose at other persons or animals.
- x **DO NOT** allow untrained persons to operate the drainer.
- x **DO NOT** operate the drainer when you are tired, under the influence of alcohol, drugs or intoxicating medication.
- x **DO NOT** leave the drainer operating unattended.
- x **DO NOT** direct air from the air hose at yourself or others.
- ✓ When not in use disconnect from the air supply, vent reservoir and store in a safe, dry, childproof area.
- ✓ Dispose of waste oil in accordance with local authority regulations.
- **WARNING!** DO NOT pollute the environment by allowing uncontrolled discharge of waste oil.
- ▲ **DANGER! DO NOT** release drain pan clamp lever when there is pressure in the reservoir as pipe and drain pan will be propelled upward with force. This could result in damage and/or serious injury.

## 2. INTRODUCTION & ASSEMBLY

### 2.1. Introduction

- 2.1.1. The AK458DX.V2 has a steel fabricated 90ltr reservoir and telescopic steel drain pan fitted with filter grid. Gravity feed reservoir with air discharge. Fitted with reservoir oil level indicator tube.


**Note:** Numbers in brackets refer to item numbers on the Parts Diagram

### 2.2. Assembly

- 2.2.1. Close all valves on the drainer.
- 2.2.2. Screw drain pan (78) outlet into ball valve (77) and tighten.
- 2.2.3. Loosen the handle retaining bolts at the back of the reservoir, insert the handle and tighten the bolts.

## 3. AIR SUPPLY

- 3.1. Ensure the air valve is in the "Off" position before connecting to the air supply.
- 3.2. You will require an air pressure of 8 - 9 bar.
- 3.3. □ **WARNING!** Ensure the air supply is clean and does not exceed pressures specified in these Instructions. Too high an air pressure and/or unclean air will shorten the drainer life due to excessive wear, and may be dangerous, causing damage and/or personal injury.
- 3.4. Drain the air tank daily. Water in the air line may damage the drainer.
- 3.5. Clean the air inlet filter screen weekly. The recommended hook-up is shown in fig.1.
- 3.6. Line pressure should be increased to compensate for unusually long air hoses (over 8 metres). The minimum hose diameter should be 10mm I.D. and fittings must have the same inside dimensions.
- 3.7. Keep hose away from heat, oil and sharp edges. Check hoses for wear, and make certain that all connections are secure.



## 4. OPERATION

- **WARNING!** Ensure that you read, understand and apply the safety instructions in Section 1.
- 4.1. Gravity
  - 4.1.1. Position drainer under vehicle, turn clamp lever (84) approximately 1/4 turn anticlockwise and raise oil pan (78) beneath drain plug.
- ▲ **DANGER! DO NOT** release clamp lever (84) when there is pressure in the reservoir as pipe (76) and oil pan (78) will be propelled upward with force. This could result in damage and/or serious injury.
- 4.2.1. Open ball valve (77) and then remove vehicle drain plug.

4.2.2. When draining is complete lower oil pan (78) before moving drainer.

**4.3. Emptying**

4.3.1. Ensure all ball valves are closed and clamp (84) is tight. Connect air supply at a pressure of 2 - 2.5 bar to coupling (16).

4.3.2. Open ball valve (71) and allow reservoir to pressurise until safety valve vents. Close ball valve (71) and disconnect air supply.

4.3.3. Place end (51) of drain tube (105) in the waste oil container and then open ball valve (69).

4.3.4. When all waste oil is displaced from reservoir any remaining air pressure will be lost. Always confirm that reservoir pressure is zero before closing valve (69). **Never leave drainer with pressure in the reservoir.**

□ **IMPORTANT! Dispose of waste oil in accordance with local authority regulations.**

**Declaration of Conformity** We, the sole UK importer, declare that the product listed below is in conformity with the following standards and directives.

The construction file for this product is held by the Manufacturer and may be inspected on request by contacting Jack Sealey Ltd.

**GRAVITY FEED/AIR DISCHARGE OIL  
DRAINER**  
**Model: AK458DX.V2**

97/23/EC Pressure Equipment Directive



Signed by Mark Sweetman

7th November 2002

*For Jack Sealey Ltd. Sole UK importer of Sealey Power Products.*

**NOTE:** It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

**IMPORTANT:** No liability is accepted for incorrect use of this product.

**WARRANTY:** Guarantee is 12 months from purchase date, proof of which will be required for any claim.

**INFORMATION:** For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.



**Sole UK Distributor, Sealey Group,**  
Bury St. Edmunds, Suffolk.



01284 757500



01284 703534

E-mail: [sales@sealey.co.uk](mailto:sales@sealey.co.uk)  
Web: [www.sealey.co.uk](http://www.sealey.co.uk)