



CAR RAMPS 1.5 TONNE CAPACITY PER RAMP 3 TONNE CAPACITY PER PAIR

MODEL NO: **CAR3000C.V2**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instructions



Wear safety footwear

1. SAFETY

- ✓ Always use on a clean, level surface; preferably a surface with some friction.
- ✓ Have a second person watching the ramps as the vehicle is driven on to warn of any unwanted movement.
- ✓ When in place, apply the vehicle handbrake and leave in gear or 'park', if an automatic.
- ✓ Always place chocks behind the rear wheels of the vehicle.
- ✗ **DO NOT** exceed the rated capacity of the ramps (1500kg each, 3000kg per pair).
- ✗ **DO NOT** use this product for any purpose other than that for which it is designed.
- ✗ **DO NOT** use the ramps if they are in any way damaged.

2. INTRODUCTION

Honeycomb design allows rain, snow and dirt to easily flow through. Stackable for minimum storage space. Easy carrying and positioning with integral handles. Curved cradle platform to retain wheel position on the ramp. Override protection to assist driving on to the ramp. Rubber feet on the base for maximum ground grip.

3. SPECIFICATION

Model No:	CAR3000C.V2
Capacity Pair:	3000kg
Maximum Tyre Width:	330mm
Nett Weight:	8.7kg
Gross Weight:	9.7kg
Overall Dimensions (L x W x H):	900 x 330 x 215mm
Ramp Height:	175mm



4. OPERATION

Apply section 1 safety instructions.

NOTE: the ramps can be used on either the front or back wheels.

- 4.1. Push the ramps as far as possible under the wheels to be lifted.
- 4.2. With a second person guiding, carefully drive the front or rear wheels up onto the ramps. Take particular care if driving a rear wheel drive vehicle, which would tend to push the ramps forward.
- 4.3. Be prepared for the possibility of the vehicle stalling and rolling back.
- 4.4. When the vehicle is safely housed on the ramps, immobilise and place chocks under the rear/front wheels.

NOTE: the wheels should sit within the curved cradle platform.

- 4.5. To dismount from the ramps, check that the area beneath the vehicle is clear and bring down very slowly using the foot brake.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR PURCHASE HERE

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on technical@sealey.co.uk or 01284 757505.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



sales@sealey.co.uk



www.sealey.co.uk