



GAS CYLINDER SAFETY CAGES

MODEL NO: **GCSC219, GCSC319, GCSC247**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instruction manual



Wear protective gloves (assembly)

1. SAFETY

- ✓ Risk assess the intended location of the gas cage with respect to the Site's Fire Safety Management Plan, to potential vehicle movements and site security requirements.
- ✓ Gas cylinder safety cage must be used in line with current HSE advice.
- ✓ The area surrounding the gas storage area should be kept clear of overhanging and adjacent vegetation (minimum distance 3m).
- ✗ **DO NOT** use weed killers to clear vegetation as there is a risk of fire.
- ✓ Safety sign must be displayed.
- ✓ All personnel accessing the cage must be adequately trained.
- ✓ Cylinders must not be subjected to adverse conditions.
- ✓ Gas cylinder safety cages must be kept clean and subjected to regular housekeeping.
- ✓ Only store gas cylinders and their associated fittings in gas cylinder safety cages. Combustible stores of any other kind must not be put with gas cylinders. A gas cylinder safety cage is NOT a store for other items.
- ☐ **WARNING!** Contact with oils, grease, hydrocarbons, tarry substances and many plastics carry the risk of spontaneous combustion, particularly with some high pressure gases.
- ✓ Gas cylinder safety cage must be fixed to the ground using bolt holes provided.
- ✓ Use protective gloves for assembly and transport.

2. INTRODUCTION

Powder coated galvanised 30mm box frame with 50mm x 50mm x 3mm wire mesh. Hinged door with hasp and staple for padlock (not provided). Pre-drilled fixing points for bolting to solid surface. Supplied flat packed for easy self-assembly using hand tools (not provided). Supplied with safety sign.

GCSC219: Suitable for up to 2 x 19kg Propane & Butane cylinders (≤ 318mm Ø).

GCSC319: Suitable for up to 3 x 19kg Propane & Butane cylinders (≤ 318mm Ø).

GCSC247: Suitable for 2 x 47kg Propane & Butane cylinders (≤ 375mm Ø).

3. SPECIFICATION

GCSC219: Dimensions (W x D x H)..... 700 x 500 x 900mm

GCSC319: Dimensions 1000 x 500 x 900mm

GCSC247: Dimensions 1000 x 500 x 1400mm

4. ASSEMBLY

- 4.1. Assemble as per picture alongside. Seek assistance from another person for assembly and siting.
- 4.2. Consider which way the door needs to open.
- 4.3. Use the shear fixings to fix the 4 walls together.
- 4.4. Fit the top section in place.
- 4.5. Fit the warning sign.
- 4.6. Shear the fixings off.
- 4.7. Securely fix to a solid surface using appropriate fixings, (not supplied).



Model no. GCSC219 shown



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



01284 703534



sales@sealey.co.uk



www.sealey.co.uk