

ALUMINIUM LOADING RAMPS 680KG CAPACITY PER PAIR

MODEL NO: LR680.V2

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



manual

1. SAFETY

- **WARNING!** Danger of serious personal injury exists when using a loading ramp. If driving up an incline ramp, training is recommended. For example, when driving up an incline with rear wheel drive, reverse up the ramp. Always have the drive wheels leading to avoid tipping.
- ✓ Regularly check the ramp for worn, loose, or damaged parts. Failure to do so may cause severe injury.
- DO NOT use if you find any of these conditions. Contact your Sealey specialist for repairs.
- **DO NOT** use ramps at a steeper angle than recommended.
 - NOTE The surface of the aluminium ramp may become slippery in icy or wet conditions. Caution should be used when using the ramp.
- √ Keep the aluminium ramp surface free of dirt and debris.
- ✓ Always check the vehicle manufacturer's recommended degree of incline.
- DO NOT add to or modify any part of the aluminium ramp; doing so will void your warranty.
- **DO NOT** use the aluminium ramp for purposes other than those it was designed for.
- ✓ Use caution when folding and unfolding your aluminium ramp. Beware of pinch points.
- ✓ Be sure that the ramp is always on a solid landing and firmly placed. Always anchor your aluminium ramp in place.
- ✓ Clean aluminium ramps with water and mild detergent.
- **WARNING!** The warnings, cautions and instructions referred to in this manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator.
- □ WARNING! DO NOT exceed maximum capacity of 680kg. (Factor in weight of driver when applicable)

2. INTRODUCTION

Manufactured from strong durable yet lightweight aluminium. Provides safe and easy ramp access for a variety of small vehicles. Suitable for loading/unloading quad bikes, ride-on lawnmowers or any other four wheeled vehicle up to a maximum of 680kg. Features extended claws at one end to help secure ramp when in use. Folding design for compact storage.


3. SPECIFICATION

Extended Dimensions (L x W x H):	2324 x 290 x 110mm
Folded Dimensions (L x W x H):	1160 x 290 x 150mm
Maximum Capacity:	680kg



Quick Reference
"H" Incline angle
1300 35°
1150 30°

975 25° 800 20° 600 15°





ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on technical esaley.co.uk or 01284 757505.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.