

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY.



Refer to instructions



Wear protective gloves



Wear protective footwear

1. SAFETY

- WARNING!** Ensure Health & Safety, and local authority regulations are adhered to when assembling and using this rack.
- Locate rack in a suitable area where it will not be an obstruction.
- Keep the general area clean, uncluttered. Ensure adequate lighting.
- WARNING!** Mount rack on a flat and solid wall such as breeze block that is strong enough to hold fully laden rack.
- The rack should be firmly secured to the wall in a suitable location with fixings provided.
- DO NOT** attempt to wall mount the rack on your own. Obtain assistance or use manual handling equipment.
- Wall mount the rack at a height that minimises the risk of injury when used.
- Keep children and unauthorised persons away from the storage area.
- DO NOT** use the rack for any purpose other than that for which it is designed.
- DO NOT** clean the rack with any solvents or abrasives which may damage the coated surface.
- DO NOT** overload the rack when mounted.
- DO NOT** climb on or attempt to stand on the rack.
- Ensure the rack is properly and firmly fitted and installed before loading.



2. INTRODUCTION

Suitable for holding up to three bumpers of various lengths for tidy workshop storage. Arms mountable in nine positions and safely foldaway when not in use so saving-space. Ideal for the busy bodyshop.

3. SPECIFICATION

Model No.: MK56.V3
Support Height 750mm
Arm Lengths 640mm
Safe Working Load: 80kg

4. ASSEMBLY

- 4.1. To fit the support arms, offer the arm up to the fixing beam.
- 4.2. Tilt arm upwards while engaging the arm pin fully through the holes in the fixing beam.
- 4.3. The arm pin is a close fit for the holes in the fixing beams. A light tap with a nylon headed mallet or similar will suffice to engage items.
- 4.4. Once fully engaged, lower the arm and locate the stop onto the fixing beam.
- 4.5. Ensure support arm pins are fully engaged and secure before loading.

5. MAINTENANCE

- 5.1. Regularly check fixings and mountings are firmly fitted and that the rigidity and security of the rack is not compromised.
- 5.2. Wipe clean with damp cloth.
 - DO NOT** use chemical or abrasive cleaners as this may result in damage to the surface.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on technical@sealey.co.uk or 01284 757505.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



01284 703534



sales@sealey.co.uk



www.sealey.co.uk