



HYDRAULIC PULLER SET 25PC WITH STORAGE CASE, 10-TONNE HYDRAULIC RAM, BEARING SEPARATOR

MODEL NO: **PS982.V3**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to
Instructions



Wear Eye
Protection

1. SAFETY

- ❑ **WARNING!** Ensure all Health and Safety, local authority, and general workshop practice regulations are strictly adhered to when using tools.
 - ✗ **DO NOT** use tools if damaged or worn.
 - ✓ Maintain the tools in good and clean condition for best and safest performance.
 - ✓ Ensure all threads are clean and well lubricated.
 - ✓ Always check that puller is correctly assembled and is square with the workpiece.
 - ✓ If vehicle is raised, ensure it is adequately supported with axle stands, ramps, etc. as appropriate.
 - ✓ Wear suitable clothing to avoid snagging. Do not wear jewellery. Tie back long hair.
 - ✓ Wear approved eye protection. A full range of personal safety equipment is available from your Sealey stockist.
 - ✓ Where possible shield workpiece with canvas or similar to provide protection against failed parts.
 - ✗ **DO NOT** heat puller jaws when heating a gear or bearing as this will affect the temper and, therefore, the strength of the material.
 - ✗ **DO NOT** use any tool or lever to turn the ram tommy bar, use hand effort only.
 - ✗ **DO NOT** hit workpiece, or ram, with a hammer if workpiece has not moved with maximum puller force applied. Use a larger capacity puller.
 - ✓ Account for all tools and parts being used and do not leave them in or on the vehicle.
- IMPORTANT:** Always refer to the vehicle manufacturer's service instructions, or proprietary manual, to establish the correct procedure and data. These instructions for use are provided as a guide only.

2. INTRODUCTION

Master set of gear pullers and bearing separators. Suitable for pulling and removing hubs, flanges and bearings. Three-leg design ensures even force distribution for more controlled removal with reduced risk of part damage. Supplied with three sets of leg sizes (100, 150, 200mm) for use on a wide range of applications. 10 Tonne hydraulic ram compatible with other sets in the Sealey range. Forged steel bearing separator for durability. Supplied in storage case.

3. CONTENTS

Refer to attached Parts List for Part Numbers and Descriptions


4. SPECIFICATION

Model No:.....PS982.V3

Contents:

10tonne Hydraulic Ram, 100mm Leg (x3), 150mm Leg (x3), 200mm Leg (x3),
Twin Head, Triple Head, Extension Rod; 25 x 50mm (x1), 25 x 100mm (x1),
Main Rod; 255mm (x4), Beam, Separator Ø75-105mm, Bolt 5/8", Ram Service Kit,
Ram Nut

Weight:..... 18.1kg



5. OPERATION

- ❑ **WARNING! Ensure that you read, understand and apply the safety instructions in Section 1.**
- 5.1. Confirm that the workpiece is retained by interference fit (parallel or taper) only.
- 5.2. Assemble the appropriate puller, see (fig.1) and adjust T-handle (fig. 2.A) so that tommy bar (fig.2.B) is approximately 80mm (3") above top of ram, see (fig.2).
- 5.3. Fit the puller claws behind the workpiece and then screw ram **body** down, with centre adaptor (item 9) over piston end, until centre adaptor point locates in end of shaft from which workpiece is to be pulled. If necessary use ram extension(s) (items 7 & 8) to achieve this.
- 5.4. Turn T-handle clockwise, by hand only, to pull workpiece from shaft, draw workpiece up shaft. Do not screw T-handle in further than 25mm (1") from end of the ram (see fig.2). If workpiece requires additional movement then unscrew T-handle to 80mm from end of ram, screw ram body down so that centre adaptor again contacts shaft and then continue to draw workpiece up shaft.
- 5.5. **IMPORTANT:** The maximum safe load for the puller can be achieved by hand effort alone.
- 5.6. **The use of tools or levers on the tommy bar to increase the load will damage the puller and may result in injury.** Such misuse will also invalidate the warranty. If the workpiece does not move, with maximum puller force applied, **DO NOT** hit it, or the puller, in an attempt to free it. Damage to puller/workpiece and personal injury may result: use a larger capacity puller.





fig.2

6. MAINTENANCE

- 6.1. **GENERAL**
- 6.2. Keep all items clean and lightly oiled. Keep all threads free from grit and lubricate the ram regularly.
- 6.2.1. Store the ram in the closed position to prevent piston surface corrosion.
- 6.3. **TO CHANGE OIL IN RAM**
- IMPORTANT:** The hydraulic system operates on a specially formulated oil which must be replaced from time to time. Use Sealey Hydraulic Jack Oil, available from your authorised Sealey stockist. Quote model number: HJO500MLS for 1 x 500ml bottle or PS982/OIL for 15gm of oil for a single refill.
- ❑ **WARNING! Use of any other oil in ram may cause ram to fail and will invalidate your warranty. Wear appropriate eye, face and hand protection.**
- 6.3.1. Dismantle by removing the ram cover (fig.3.2) with soft jaw grips (fig.3.A) (body may have to be held in a soft jaw vice, ensure bodythread is not damaged).
- ▲ **Caution! The cover is spring loaded, take care when removing. Remove components 2, 3, and 4 from the cylinder carefully.**
- 6.3.2. Screw T-handle (fig.4.5) down as far as it will go, then unscrew and remove it from the body (fig.4.5).
- 6.3.3. Push a narrow screw driver (fig.4.9), or a rod of appropriate diameter, down the small opening in head of ram (B), in order to push components 6, 7, and 8, plus the oil, out of the main cylinder.
- NOTE:** A medium force may be required.
- 6.3.4. Remove remaining oil from main cylinder.
- 6.3.5. Take the small seal and piston (fig.5.7 & 8) and gently push them down the narrow bore of the cylinder ensuring the metal piston (8) is first, with the concave face pointing in the direction of the T-handle, and the seal (fig.5.7) second, with the widest part of the seal facing upwards towards the main cylinder (fig.5). Push into bore as far as possible.




fig.3




fig.4




fig.5




fig.6




fig.7




fig.8

- 6.3.6. Pour 15gm of oil into the bore (fig.6). Insert the larger seal (fig.7.6) as shown, with the widest part of the seal facing downwards into the bore. Push down into main cylinder as far as 'X' (fig.7) followed by piston (fig.7.4) and spring (fig.7.3).
- 6.3.7. Refit (do not overtighten) ram cover (fig.7.2) and replace T-handle (fig.7.5).
- **WARNING!** The correct orientation of pistons and seals in the ram is critical.
- 6.3.8. Screw T-handle into ram until it contacts small piston and then turn a further two or three times.
- 6.3.9. Remove T-handle and firmly bounce the ram piston (fig.8) on a hard, but non-damaging, surface 6 to 10 times to consolidate the oil.
- 6.3.10. Replace the T-handle, wipe clean and the ram is ready for use.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR
PURCHASE HERE

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on technical@sealey.co.uk or 01284 757505.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Jack Sealey Ltd t/a Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk, IP32 7AR UK
Jack Sealey (EU) Ltd t/a Sealey Group, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland
Tel: 01284 757500 • **Email:** sales@sealey.co.uk • **Web:** www.sealey.co.uk