



INSTRUCTIONS FOR:
TOPCHEST 660MM HEAVY DUTY
MODEL No: **PTB660TR**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY

1.1. GENERAL SAFETY

- WARNING!** Ensure Health & Safety, local authority, and general workshop practice regulations are adhered to when using this topchest.
- ✓ Locate the topchest in a suitable work area.
- ✓ Keep the work area clean, uncluttered and ensure there is adequate lighting.
- ✓ Keep topchest clean and tidy in accordance with good workshop practice.
- ✓ Keep children and unauthorised persons away from the work area.
- x **DO NOT** use this topchest for any purpose other than that for which it is designed.
- x **DO NOT** clean the topchest with any solvents which may damage the surfaces or the protective coating.

2. INTRODUCTION

Innovative, heavy-duty, wedge shaped topchest/tool organiser with lift-open front cover. Allows optimization of storage with instant visual on tools. The cover is designed to prevent tools becoming dislodged as it holds them in place when shut. A heavy-duty weather strip also protects tools from dust and moisture. Suitable to be transported beyond the workshop without the worry of tool disruption or damage from the elements. Powder coated in a textured finish fitted with sturdy side handles. Heavy-duty lock with two keys. Can be used in conjunction with model no. PTB67506 roll cab or can be used free standing.

3. SPECIFICATION

Model No. **PTB660TR**
Overall Size W x D x H: 680 x 442 x 460mm

4. OPERATION

- 4.1. This topchest is heavy, obtain the help of at least one other person before attempting to unpack it.
- 4.2. Lift tab to open door. Pull up bottom lip of socket storage tray to access back storage area, gently push down again to close.
Note: top row of storage hooks must not be used for socket storage as this will prevent door from closing.
- 4.3. Push door firmly to close it as weatherproof seal needs to be compressed fully.



Parts support is available for this product. To obtain a listing and/or diagram, please log on to: www.sealey.co.uk,
email: sales@sealey.co.uk or phone: 01284 757500



Environmental Protection.

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycle centre and disposed of in a manner which is compatible with the environment.

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.



Sole UK Distributor, Sealey Group,
Kempson Way, Suffolk Business Park,
Bury St. Edmunds, Suffolk,
IP32 7AR



01284 757500

01284 703534



www.sealey.co.uk

sales@sealey.co.uk