

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- ✓ Familiarise yourself with the application and the limitations and potential hazards of the rack.
- ✓ Maintain the rack in good condition (use authorised replacement parts).
- ✓ Keep the rack clean for best and safest performance.
- ✓ Locate the rack in a suitable work area.
- ☐ **WARNING!** Use the rack on level and solid ground, preferably concrete.
- ✗ **DO NOT** overload the rack.
- ✗ **DO NOT** climb on the rack.
- ✗ **DO NOT** use the rack for any purpose other than for which it is designed.
- ✗ **DO NOT** use the rack if any parts are damaged or missing as this may cause failure and/or personal injury.
- ✓ Keep the work area clean, uncluttered and ensure that there is adequate lighting.
- ✓ Keep children and unauthorised persons away from the work area.

2. INTRODUCTION

Safe and tidy workshop storage for up to 6 painted bumpers. Prevents inadvertent damage to paint finish during storage. Six pairs of removable support arms for maximum capacity and flexibility. Fitted with four braked castors for maximum manoeuvrability and safe positioning.

3. ASSEMBLY INSTRUCTIONS

- 3.1. Check that all contents are present and familiarise yourself with the parts.
- 3.2. Bolt the 2 foot bars and 1 middle bar together to form the base.
- 3.3. Position 1 bottom bar onto one of the foot bars making sure that it is angled backwards towards the back of the base (short length). Repeat with the other bottom bar and foot bar.
- 3.4. Bolt the top bars to the top of the bottom bars and then bolt the remaining middle bar in between these.
- 3.5. Starting from the bottom, bolt each supporting bar to the respective holder, working methodically upwards on each level.
- 3.6. Bolt the 4 castor wheels to the foot bars.
- 3.7. Insert all end caps.

