

1L PREMIUM PRESSURE SOLVENT SPRAYER WITH VITON® SEALS

MODEL NO: SCSG04

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



1. SAFETY

- □ WARNING! Wear approved eye protection. Wear appropriate Personal Protective Equipment. A full range of Personal Protective Equipment is available from your Sealey stockist.
- □ WARNING! Ensure that Health & Safety, Local Authority Regulations and general workshop practice Regulations are adhered to when using sprayer.
- ✓ Be aware of the safety requirements for the fluids contained in the vessel.
- ✓ Read and follow all the fluid manufacturers instructions for application and safe use.
- ✓ Store the sprayer out of reach of children.
- Label vessel with chemical used, even if water. It is highly recommended that individual vessels should be used for individual chemicals. Cross contamination can give unexpected results.
- * DO NOT spray at people, animals, in high winds, or where there are sources of ignition.
- **DO NOT** use the pressure sprayer for any purpose other than for which it is designed.
- * DO NOT use whilst eating, drinking, smoking; under the influence of drugs, alcohol, intoxicating medication, or if fatigued.
- **DO NOT** leave the tank pressurised for long periods of time.
- * DO NOT expose the sprayer to direct sunlight.
- DO NOT fill the container with liquids exceeding 30°C.

2. INTRODUCTION

Premium quality hand pump sprayer. Suitable for use with most brake cleaners, detergents, traffic film removers, penetrating oils and weed killers. Viton® seals allow use with a wide range of semi volatile chemicals that would deteriorate standard seals. Adjustable nozzle enables a mist to jet pattern, which allows an easy and direct application of liquid exactly where it is required. Robust composite construction.

3. PREPARATION

- 3.1. Check before use that all parts are undamaged and are working correctly.
- **3.2.** Unscrew the pump from the tank.
- 3.3. Fill the canister to the required level, 'max' for best results.
- **3.4.** Screw the pump head on and tighten it so that the canister is sealed and airtight (if it is not airtight it will be impossible for pressure to build up).

4. OPERATION

4.1. Pump the air into the tank using the piston (20 to 30 movements, if tank filled to the 'max').

IMPORTANT! It is not possible to generate too much pressure in the tank. The sprayers are fitted with an automatic relief valve.

- 4.2. To spray press down the spray button. Turn the spray nut on the end of the nozzle, to set the desired spray pattern from mist to jet.
- **4.3.** If liquid continues to drip out of the nozzle after releasing the spray button, there is still air in the sprayer. Spray upwards at an incline for 2 to 3 seconds to enable the air to escape.
- 4.4. The ability to spray evenly and without any problems is dependent on the use of a clean spray agent.
- **4.5.** Mix chemical and water (if required) thoroughly prior to filling the container, taking note of the usage instructions of the chemical manufacturer.

4.6. AFTER USE

- 4.6.1. After spraying unscrew the spray head slowly to allow the pressure to escape. Never leave the tank pressurised for long periods of time. Dispose of any residues in accordance with local authority regulations.
- 4.6.2. Clean the pump by spraying with water or use a suitable cleaning agent.

5. MAINTENANCE

- 5.1. Oil the pump piston occasionally (see arrow on spray button).
- 5.2. Check that the nozzle and the filter at the end of the pick up hose is free of deposits and clean if necessary.
- 5.3. A kit of new seals for the sprayer is available from your Sealey stockist quote part no. SCSGPRK.





ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR 01284 757500 Representation of the sealey.co.uk www.sealey.co.uk

Original Language Version