



KEVLAR® HOT SLEEVES

MODEL NO: **SSP36 & SSP37**



Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Read instructions before use



1. INTRODUCTION

Manufactured to CAT 2 BS EN 388 and BS EN 407 from 100% DuPont Kevlar®. Designed for use in engine bays to prevent cuts to forearms and burns from exhausts and other hot components. Thumb slot design ensures sleeve will stay in position. Certified to EN 12477, Type 'A'.

2. SAFETY

NOTE: These sleeves have been designed to protect against primarily mechanical risks as defined by Regulation (EU) 2016/425 and Module B of Regulation 2016/425 on personal protective equipment, as amended to apply in GB. They are in compliance with and are labelled according to the requirements of the PPE Regulation and subsequent amendments and comply with the applicable technical European Standards detailed in this document. Jack Sealey Limited will not be held responsible for the improper use of the product for non-designated purposes. Assess your actual workplace conditions to determine if the sleeves are appropriate for the specified use.

2.1. PRECAUTIONS FOR USE

- WARNING! DO NOT** bring the sleeves into contact with a naked flame or fire.
- WARNING!** Whilst these sleeves are highly cut resistant, they are not cut proof.
- × **DO NOT** use these sleeves with chemicals.
- × **DO NOT** use when there is a risk of entanglement with moving machine parts.
- × **DO NOT** subject to high speed or serrated blades.
- ✓ Inspect the sleeves for defects before each use.
- ✓ Replace damaged, dirty or worn out sleeves.
- ✓ Clean the sleeves after use, as used sleeves may be contaminated with infectious or hazardous materials.

2.2. CONSTITUENTS/ALLERGIES

2.2.1. Some sleeves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur, seek medical advice Immediately.

NOTE: This model does not contain any substances at levels that are known to, or suspected to adversely affect user hygiene or health.



This data may not reflect actual duration of protection in the workplace due to factors such as temperature, abrasion and degradation etc. The result of the laboratory tests should help with correct products election, however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine suitability for the intended use.

2.3. Protection against risks or hazards not mentioned In this document is not warranted.

2.4. The levels of performance mentioned are only valid for new sleeves.

2.5. You are advised to retain this information for future reference.

3. PERFORMANCE

Mechanical Hazard EN 388 : 2016  1343C	Abrasion Resistance	1	(on 4 maxi)	'X' indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material. Testing carried out on the arm material of the sleeve.
	Blade Cut Resistance	3	(on 5 maxi)	
	Tear Resistance	4	(on 4 maxi)	
	Puncture Resistance	3	(on 4 maxi)	
	TDM Cut (ISO 13997) (A-F)	C	(A to F)	
Thermal Risk EN 407 : 2020  X1XXXX	Burning Behaviour	X	(on 4 maxi)	
	Contact Heat	1	(on 4 maxi)	
	Convective Heat	X	(on 4 maxi)	
	Radiant Heat	X	(on 4 maxi)	
	Small Splashes of Molten Metal	X	(on 4 maxi)	
Large Quantities of Molten Metal	X	(on 4 maxi)		

4. MAINTENANCE

4.1. CLEANING

- × **DO NOT** use with chlorine bleaches.
- × **DO NOT** wash or dry clean this product.

NOTE: The performance results are for products in a new condition only and Jack Sealey Limited cannot accept any liability if the sleeves do not have the same levels of performance after washing.

4.2. STORAGE

- ✓ Store the gloves in their original packaging.
- ✓ Store away from direct sunlight, in a cool, dry place.
- ✓ Store the gloves in clean, covered and ventilated premises.

4.3. MAINTENANCE

- ✓ The gloves should be inspected before each use, and replaced if damaged.

5. OBSOLESCENCE

Service life cannot be specified and depends on the application and responsibility of user to ascertain suitability of the sleeve for its intended use. In any case, this PPE is subject to ageing and has a 3 year shelf life when stored in appropriate conditions.

This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at www.sealey.co.uk.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR PURCHASE HERE

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

EU | Sealey EU Ltd, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

UK | Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



sales@sealey.co.uk



www.sealey.co.uk