

2-IN-1 PEN LIGHT & TYRE PRESSURE GAUGE

MODEL NO: TSTPL01

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY

- ✓ Keep the gauge out of reach from children.
- DO NOT look directly into the beam of light, as this will result in dazzling.
- **x DO NOT** use the lamp near a naked flame
- **x DO NOT** disassemble, repair or alter the gauge.
- DO NOT operate the gauge with wet hands.

2. INTRODUCTION

Digital tyre pressure gauge displayed in bar, psi, kPa and kg/cm². Bright LCD backlit display, ideal for reading the screen in low light conditions. Main side light COB LED 2W 180 lumens (worklight)/90 lumens (low light). Top Light SMD LED, 1W 80 lumens. 3.7V Rechargeable 500mAh Lithium-ion battery with a USB Type-C charging cable. Base and side magnets for easy hands-free use. It can be easily stored in a glove box.

3. SPECIFICATION

Model No:	TSTPL01
Pressure Units:	Bar, psi, kPa, kg/cm²
Range:	0.21-10.3bar(3-150psi, 0.21-10.5kg/cm², 21-1034kPa)
Resolution:	0.5psi
Battery Type	3.7V 500mAh
Input (USB Type-C)	5V (dc) 1A
Charge Time	1hr
Work light Source	2W COB LED
Work light Brightness	Work light 180 lumens/low light 90 lumens
Work light Runtime	2hrs main work light
Torch Source	1W SMD
Torch Brightness	80 lumens
Product Dimensions (L x D x W)	170mm x 22mm x 30mm
USB Type C Cable Length	400mm



4. OPERATION

4.1. CHARGING THE GAUGE

- 4.1.1. Connect the USB cable to the USB INPUT on the side of the light.
- 4.1.2. Plug the USB cable into a suitable 5V-1A outlet or mains adapter (not included). **NOTE:** ensure the light is turned OFF whilst charging.

4.2. OPERATING THE LIGHT

- 4.2.1. Press the TORCH button to cycle between the torch and the main light.
- 4.3. MEASURING TYRE PRESSURE
- 4.3.1. Press the PRESSURE button to turn on the unit.
- 4.3.2. Press the PRESSURE button to cycle between the following units: PSI, BAR, KPA, Kg/cm².
- 4.4. Align the tyre pressure gauge with the valve of the tyre and press it tightly for 3 seconds. The correct pressure will display.
- 4.4.1. Hold the PRESSURE button to turn the unit off, or wait 30 seconds for the unit to turn off automatically.

5. MAINTENANCE

- × DO NOT leave the battery without charge for an extended period deep discharge risks damaging the battery
- * The light source is not replaceable; when the light source reaches its end of life the whole product shall be replaced.



WEEE REGULATIONS

Dispose of this product at the end of its working life in compliance with the EU Directive on Waste Electrical and Electronic Equipment (WEEE). When the product is no longer required, it must be disposed of in an environmentally protective way. Contact your local solid waste authority for recycling information.



BATTERY REMOVAL

Under the Waste Batteries and Accumulators Regulations 2009, Jack Sealey Ltd are required to inform potential purchasers of products containing batteries (as defined within these regulations), that they are registered with Valpak's registered compliance scheme. Jack Sealey Ltd Batteries Producer Registration Number (BPRN) is BPRN00705.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR 01284 757500 R sales@sealey.co.uk r www.sealey.co.uk