# OIL CAPTURE EXTENSION FUNNEL SET

MODEL NO: VS409

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.











footwear



Refer to instructions

Wear eye protection

aloves

Wear protective Wear protective clothing

# SAFETY

- WARNING! Ensure Health & Safety, local authority, and general workshop practice regulations are adhered to when using this equipment.
- Familiarise yourself with the application and limitations of the oil extension funnel, as well as the potential hazards.
- Ensure Proper Ventilation: Work in a well-ventilated area to avoid inhaling fumes.
- Avoid Contact with Hot Engine Parts: Ensure the engine has cooled down before handling the oil filter.
- Keep the Work Area Clean: Wipe up any spills immediately to prevent slipping hazards.
- Secure the Funnel: Make sure the funnel is properly attached to prevent leaks and spills.
- Replace or repair damaged parts. Use genuine parts only. Unauthorised parts may be dangerous and will invalidate the warranty.
- Keep the work area clean, uncluttered and ensure there is adequate lighting. Observe work area conditions. Keep area well lighted.
- DO NOT modify the oil funnel and DO NOT use the funnel for a purpose for which it was not intended.
- DO NOT operate the oil funnel if any parts are damaged before using any product. Any part that appears damaged should be carefully checked to determine that it will operate properly and perform its intended function. Use of any other parts will void the warranty.
- DO NOT operate the oil funnel when you are tired, under the influence of alcohol, drugs or intoxicating medication.
- WARNING! Use eye protection. Always wear ANSI-approved impact safety goggles or a full face shield when working with this product.
- Dress safely. Non-skid footwear or safety boots should be used when working with the product.
- DO NOT allow children in the work area.
- Always check hardware and assembled parts after assembling. All connections should be tight and hardware tightened.
- DO NOT overreach. Keep proper footing and balance at all times to prevent tripping, falling and injury.
- Dispose of waste oil in accordance with local authority regulations.
- Keep the oil funnel clean for best and safest performance.
- DO NOT place attachments close to your face.
- × DO NOT allow untrained persons to operate the oil funnel.
- × DO NOT attach to impact tools.
- WARNING! DO NOT pollute the environment by allowing uncontrolled discharge of waste oil.
- WARNING! Never use unit for handling highly volatile fuels and fluids
- WARNING! Never fill the funnel over the maximum level indicated by the level indicator.
- WARNING! When extracting high temperature oils ensure that hands and face are protected using suitable PPE.

#### 2. INTRODUCTION

Designed to capture oil spillage when removing oil filters. The long reach extension bar and oil seal contain waste oil. The pouring spout makes waste oil disposal easy. Spill-proof oil filter removal. Protects the technician's hands from hot oil during the oil filter removal process. Oil funnel capacity: 1L. 300mm 3/8"Sq Drive extension bar that connects to any oil filter wrench (wrench not included). The set also includes a 3/8" to 1/2" Adaptor.

# 3. SPECIFICATION

Model No:	VS409
Oil funnel capacity	1L
Nett Weight	0.45kg



## 4. OPERATION

- 4.1. Position the Funnel: Place the extension funnel directly beneath the oil filter before loosening it. Make sure it aligns with the direction of oil flow to prevent spills.
- 4.2. Loosen the Oil Filter: Using an oil filter wrench, slowly loosen the filter. The used oil will begin draining through the funnel.
- 4.3. Direct the Oil Flow: The extension funnel guides oil into the container. Ensure your funnel is properly positioned to catch all the draining oil.
- 4.4. Fully Remove the Filter: Once the majority of oil has drained, completely unscrew the filter and allow any remaining oil to drip through the funnel.
- 4.5. Dispose of Used Oil Properly: Once draining is complete, dispose of the used oil and filter according to environmental regulations.
- 4.6. Clean the Funnel: Wipe the funnel with a rag or a degreaser to prevent contamination when using it next time.
- 4.7. When not in use the main cup and extension rod should be separated to prevent gasket deformation causing oil leakage.

## 5. MAINTENANCE

5.1. Clean the Funnel: Wipe the funnel with a rag or a degreaser to prevent contamination when using it next time. When not in use store in a cool, dark place and out of direct sunlight.



# **ENVIRONMENT PROTECTION**

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice

**Important**: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Jack Sealey Ltd t/a Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk, IP32 7AR UK Jack Sealey (EU) Ltd t/a Sealey Group, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland
Tel: 01284 757500 • Email: sales@sealey.co.uk • Web: www.sealey.co.uk

© Jack Sealey Limited Original Language Version VS409 Issue 2 19/11/25