



INSTRUCTIONS FOR MOTORCYCLE FRONT WHEEL CHOCK

MODEL NO: **WCT02**

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instruction manual



Wear protective gloves



Wear protective footwear

1. SAFETY

- WARNING!** The warnings, cautions and instructions referred to in this manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator. It is the operator's responsibility to secure the load. Check with vehicle manufacturer's Manual before installing.
- WARNING!** Before use, ensure that there is nothing attached to the front forks or the fairing of the motorcycle, that will foul on the chock.
- Proper use and installation of this product is critical to safety. Improper use may result in personal or property damage which is not covered by the warranty.
- Proper care and maintenance of the chock is critical to safety.
- Keep the chock clean for the best and safest performance.
- Maintain correct balance and footing whilst positioning the motorcycle in the chock.
- Ensure that the floor is not slippery and wear non-slip shoes.
- Ensure that the motorcycle is adequately secured to the chock if to be used for transportation purposes. Consideration should also be given to securing the rear wheel as well.
- Keep children and unauthorised persons away from work area.
- Inspect chock before each use. Check fasteners for tightness, replace any worn or damaged parts.
- Before removing a motorcycle from the chock, ensure that there are no obstructions or persons in the path of the motorcycle.
- DO NOT** attempt to use a chock that is damaged in any way.
- DO NOT** modify the chock in any way.
- DO NOT** use the chock for a purpose it is not designed to perform.
- DO NOT** operate the chock if it is damaged.
- DO NOT** use the chock when you are tired or under the influence of alcohol, drugs or intoxicating medication.
- DO NOT** allow untrained persons to use the chock.

2. INTRODUCTION

Black powder coated heavy-duty tubular frame. Pre-drilled holes allow chock to be bolted to the floor of a vehicle or trailer bed to prevent movement and maintain balance. Suitable for motorcycles with up to 170mm wide tyres.

3. SPECIFICATION

Model No.: WCT02
Minimum/Maximum Tyre Width 50/170mm



4. INSTALLATION

- 4.1. Identify and drill the three 10mm (3/8") diameter chock mounting holes. The wheel chock can be used as a template for marking out.
- 4.2. The mounting holes of the chock frame are square to enable the use of the supplied coach bolts which, having a short square shank behind the head, prevent the bolts from rotating whilst the fixings are tightened. Check with vehicle/trailer manufacturer's Manual before installing to ensure the most secure location.
- 4.3. When used for the transport of motorcycles, the chock must be firmly bolted to the floor of a trailer or van. If mounting to a trailer or other vehicle, ensure that the floor is strong enough to take the weight of the motorcycle/s plus the chock/s.

5. OPERATION

- WARNING! DO NOT** sit on the motorcycle when it is mounted in the wheel chock.
- 5.1. When transporting motorcycles consideration should also be given to securing the rear wheel as well as securing the front wheel with belts or straps (not supplied).
 - 5.2. Check for loose fittings or damaged parts before each use.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



01284 703534



sales@sealey.co.uk



www.sealey.co.uk