



Section 1. Product and Company Identification.

1.1 Model Number; SCS060 v1
1.2 Description; Stone Chip Paint 500ml – Pack of 6
 500ml Paint

1.3 Manufacturer;

Sealey Group.
 Kempson Way,
 Bury St. Edmunds,
 Suffolk.
 IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 22nd June 2022

Section 2. Hazards Identification.

2.1 Classification of the substance or mixture.

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

2.2 Label elements.

Hazard pictogram(s)



Signal Word. Danger

Hazard statements;

H222 - Extremely flammable aerosol.
 H229 - Pressurised container: May burst if heated.
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation.
 H336 - May cause drowsiness or dizziness.
 H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements;

P102 - Keep out of reach of children.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P271 - Use only outdoors or in a well-ventilated area.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °

2.3 Other hazards.

Contains no PBT/vPvB substances.



Section 3. Substances.

3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Volume	Classification	
			Hazard Class & Category Code	Hazard Statements ¹
Acetone	67-64-1	30 – 50 %	Flam. Liq. 2 STOT SE 3 Eye Irrit. 2	H225 H336 H319
Petroleum Gases, Liquefied	68476-85-7	10 – 30 %	Flam. Gas 1 Press. Gas Carc. 1A Muta. 1B	H220 H350 H340
Xylene	1330-20-7	10 – 30 %	Flam. Liq. 3 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2	H226 H332 H312 H315
Ethyl Methyl Ketone	78-93-3	1 – 10 %	Flam. Liq. 2 STOT SE 3 Eye Irrit. 2	H225 H336 H319
Zinc Oxide	1314-13-2	< 1 %	Aquatic Acute 1 Aquatic Chronic 1	H400 H410
2-Ethylhexanoic acid, Zirconium Salt	22464-99-9	< 1 %	-	-

¹For full text of Statements, see Section 16.



Section 4. First Aid Measures.

4.1 Description of first aid measures

Inhalation

Remove person to fresh air.

Seek medical attention

Skin Contact

Wash skin with plenty of water.

Take off contaminated clothing.

If skin irritation occurs, seek medical attention

Eye Contact

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do.

If eye irritation persists, seek medical attention

Ingestion

Immediately seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Irritation.

Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

Section 5. Fire Fighting Measures.

5.1. Extinguishing media

Water spray, Dry powder, Foam, Carbon dioxide

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Toxic fumes may be released.

5.3. Advice for fire-fighters

Do not attempt to take action without suitable protective equipment.

Self-contained breathing apparatus.

Complete protective clothing.



Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate spillage area.

No open flames, no sparks, and no smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Avoid release to the environment

6.3. Methods and material for containment and cleaning up

Mechanically recover the product.

6.4. Reference to other sections

See Section 7 for information on Safe Handling

See Section 8 for information of Personal Protective Equipment.

See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well-ventilated area.

Avoid contact with skin and eyes. Wash hands after handling the product.

Wear personal protective equipment. Wash contaminated clothing before reuse.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Protect from sunlight.

Do not expose to temperatures exceeding 50 °C/ 122 °F.

Store locked up.

Store in a well-ventilated place.

Keep container tightly closed.

Keep cool.

7.3. Specific end use(s)

Intended for use as paint for the Model Number identified in 1.1 with Description stated in 1.2.



Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters

Workplace exposure limits.

Substance	CAS number	Workplace exposure limit.			
		Long term.		Short term.	
		ppm	mg.m ³	ppm	mg.m ³
Acetone	67-64-1	500	1210	1500	3620
Petroleum Gases, Liquefied	68476-85-7	1000	1750	1250	2180
Xylene	1330-20-7	50	220	100	441
Ethyl Methyl Ketone	78-93-3	200	600	300	899

8.2. Exposure controls

Appropriate Engineering Controls

Ensure good ventilation of the work station

Eye/Face Protection

Use of correct safety glasses

Skin Protection

Wear suitable protective clothing and gloves.

Respiratory Protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance:	Black Liquid
(b) Odour:	Characteristic
(c) Odour threshold;	No data available
(d) pH:	No data available
(e) Melting point/freezing point;	No data available
(f) Initial boiling point and boiling range;	No data available
(g) Flash point;	< 23°C
(h) Evaporation rate;	No data available
(i) Flammability (solid, gas);	Extremely flammable aerosol
(j) Upper/lower flammability or explosive limits;	No data available
(k) Vapour pressure;	No data available
(l) Vapour density;	No data available
(m) Relative density;	No data available
(n) Solubility(ies);	No data available
(o) Partition coefficient: n-octanol/water;	No data available
(p) Auto-ignition temperature;	No data available
(q) Decomposition temperature;	No data available
(r) Viscosity;	No data available
(s) Explosive properties;	May burst if heated
(t) Oxidising properties.	No data available

9.2 Other information

No data available



Section 10. Stability and Reactivity.

10.1. Reactivity	Extremely flammable aerosol. May burst if heated
10.2. Chemical stability	Stable under normal conditions
10.3. Possibility of hazardous reactions	No dangerous reactions known under normal conditions
10.4. Conditions to avoid	Avoid hot surfaces, heat, flames, and sparks.
10.5. Incompatible materials	No data available
10.6. Hazardous decomposition products	Under normal conditions, hazardous decomposition products should not be produced.

Section 11. Toxicological Information.

- 11.1.** Information on toxicological effects
- Skin corrosion / irritation : Causes skin irritation
- Serious eye damage / irritation : Causes serious eye irritation
- STOT – single exposure : May cause drowsiness or dizziness

Section 12. Ecological Information.

- 12.1.** Toxicity
- Ecology – General : Harmful to aquatic with long lasting effects
- Hazardous to the aquatic environment – short term : Not classified
- Hazardous to the aquatic environment – long term : Harmful to aquatic with long lasting effects.
- | | |
|---|-------------------|
| 12.2. Persistence and degradability | No data available |
| 12.3. Bioaccumulative potential | No data available |
| 12.4. Mobility in soil | No data available |
| 12.5. Results of PBT and vPvB assessment | No data available |
| 12.6. Other adverse effects | No data available |

Section 13. Disposal Considerations.

- 13.1.** Waste treatment methods
- Dispose of in accordance with local authority regulations.



Section 14. Transport Information.

ADR. International Carriage of Dangerous Goods by Road.

14.1. UN number	UN 1950
14.2. Name and Description	AEROSOLS, flammable
14.3. Transport hazard class(es)	2
14.4. Packing group	-
14.5. Environmental hazards	Does not present an environmental hazard.
14.6. Special precautions for user	No special precautions necessary.

IATA. International Air Transport Association.

14.1. UN number	UN 1950
14.2. UN Proper Shipping Name/Description	AEROSOLS, flammable
14.3. Transport hazard class(es)	Division 2.1
14.4. Packing group	-
14.5. Environmental hazards	Does not present an environmental hazard.
14.6. Special precautions for user	No special precautions necessary.

IMDG. International Maritime Dangerous Goods.

14.1. UN number	UN 1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	2
14.4. Packing group	-
14.5. Environmental hazards	Does not present an environmental hazard.
14.6. Special precautions for user	No special precautions necessary.
14.7. Transport in bulk – Maritime only.	Bulk transport is not applicable to this product

Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Explosive Precursors Regulation (2019/1148)

Name	CAS-No	Combined Nomenclature Code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	Ex 3824 99 92

Drug Precursors Regulation (273/2004)

Name	CN Designation	CAS-No	CN Code	Category	Threshold	Annex
Acetone	-	67-64-1	2914 11 00	Category 3	-	Annex I
Methyl Ethyl Ketone	Butanone	78-93-3	2914 11 00	Category 3	-	Annex I

15.2. Chemical safety assessment

No data available



Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H336 May cause drowsiness or dizziness
- H340 May cause genetic defects
- H350 May cause cancer.
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	23/09/22	First issue.

End of Safety Data Sheet.