Section 1. Product and Company Identification.

1.1 Model Number; SCS105 v1

1.2 Description; Glue Removal Fluid 200ml

Unique Formula Identifier (UFI): M8U0-60VY-M00W-GM4S

1.3 Manufacturer;

Jack Sealey Ltd.
t/a Sealey Group.
Kempson Way,
Bury St. Edmunds,
Suffolk,
IP32 7AR
UK

Jack Sealey (EU) Ltd
t/a Sealey Group.
Farney Street,
Carrickmacross,
Co. Monaghan,
A81 PK68
Ireland

technicalcompliance@sealey.co.uk

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 28/09/2026

Section 2. Hazards Identification.

2.1 Classification of the substance or mixture.

Skin Irrit. 2	Causes skin irritation
Eye Irrit. 2	Causes serious eye irritation
Asp. Tox. 4	Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

2.2 Label elements.

UFI. M8U0-60VY-M00W-GM4S

Hazard pictogram(s)



Signal Word. Danger

Hazard statements;

Causes skin irritation
Causes serious eye irritation
May be fatal if swallowed and enters airways

Section 2. Hazards Identification continued.

Precautionary statements;
Keep out of reach of children
Wear protective gloves and eye protection
Wash hands thoroughly after handling
IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
If skin irritation occurs: Get medical advice
Dispose of contents/container in accordance with local regulations

2.3 Other hazards.
Contains hydrocarbons which may cause aspiration into the lungs.
This mixture does not contain substances identified as PBT or vPvB.

Section 3. Substances.

3.1 Chemical Name (substance)	**3.1 CAS No.**	**3.2 Concentration Volume**	**Classification**	
			Hazard Class & Category Code	**Hazard Statements [1]**
Hydrocarbon, C11–C14, n-alkanes, isoalkanes	64742-47-8	80 – 90%	Asp. Tox. 1	H304
Xylene	1330-20-7	4 - 7%	Skin Irrit. 2 Eye Irrit. 2	H315 H319
2-Butoxyethanol	11-76-2	4 – 7%	Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Skin Irrit. 2 Eye Irrit. 2	H302 H312 H332 H315 H319
Amides, C8–18, N,N-bis(hydroxyethyl)	68155-07-7	0.7 – 1%	Skin Irrit. 2 Eye Irrit. 2	H315 H319
Benzenesulfonic acid, C10–13, TEA salt	84961-74-0	0.7 – 1%	Skin Irrit. 2 Eye Dam. 1	H315 H318
Alcohols, C12–14, ethoxylated, sulfates, sodium salts	68891-38-3	0.7 – 1%	Skin Irrit. 2 Eye Dam. 1	H315 H318

[1]For full text of Statements, see Section 16.

Section 4. First Aid Measures.

4.1 Description of first aid measures

First Aid measures, general. Call a poison centre or a doctor if unwell. Quote UFI in Section 1.2.

Inhalation
Move to fresh air. Seek medical attention if symptoms persist.

Skin Contact
Wash with plenty of water. Remove contaminated clothing.

Eye Contact
Rinse cautiously with water for several minutes. Remove contact lenses if present.

Ingestion
Rinse mouth. Do not induce vomiting. Seek medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed
Eye damage, irritation, allergic skin reaction, gastrointestinal discomfort.

4.3. Indication of any immediate medical attention and special treatment needed
Treat symptomatically.

Section 5. Fire Fighting Measures.

5.1. Extinguishing media
Foam. CO_2. Dry chemical.

5.2. Special hazards arising from the substance or mixture
Vapours may form explosive mixtures with air

5.3. Advice for fire-fighters
Wear full protective equipment.

Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures
Use Personal Protective Equipment.
Remove sources of ignition.

6.2. Environmental precautions
Prevent entry into drains and water courses.

6.3. Methods and material for containment and cleaning up
Absorb with inert material.

6.4. Reference to other sections
See Section 7 for information on Safe Handling
See Section 8 for information of Personal Protective Equipment.
See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling
Ensure adequate ventilation.
Prevent breathing spray.
Prevent contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities
Store in a cool, ventilated area.
Keep container tightly closed.

7.3. Specific end use(s)
Intended for use as Glue Removal Fluid, Model Number identified in 1.1 with Description stated in 1.2.

Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters

Workplace exposure limits.

	Short Term Exposure Limit	Time Weighted Average
Xylene	100 pm	50 ppm
2-Butoxyethanol	50 ppm	25 ppm

ppm: Parts Per Million

8.2. Exposure controls
Appropriate Engineering Controls
Ensure adequate ventilation.

Eye/Face Protection
Chemical resistant goggles or face shield.
Prevent contact with skin.

Skin Protection
Chemical resistant clothing.
Nitrile gloves.

Respiratory Protection
Organic vapour mask.
Ensure adequate ventilation.

Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance:	Liquid. Clear
(b) Odour:	Strong solvent.
(c) Odour threshold;	Not applicable.
(d) pH:	Not applicable.
(e) Melting point/freezing point;	No data available.
(f) Initial boiling point and boiling range;	Not applicable.
(g) Flash point;	Typically >60°C
(h) Evaporation rate;	Not applicable.
(i) Flammability (solid, gas);	No data available.
(j) Upper/lower flammability or explosive limits;	No data available.
(k) Vapour pressure;	Not applicable.
(l) Vapour density;	Not applicable.
(m) Relative density;	~0.78–0.82
(n) Solubility(ies);	Insoluble in water
(o) Partition coefficient: n-octanol/water;	No data available.
(p) Auto-ignition temperature;	No data available.
(q) Decomposition temperature;	Not applicable.
(r) Viscosity;	Low.
(s) Explosive properties;	No data available.
(t) Oxidising properties.	No data available.

9.2 Other information -

Section 10. Stability and Reactivity.

10.1. Reactivity	Not reactive under normal conditions of use.
10.2. Chemical stability	Stable under normal conditions.
10.3. Possibility of hazardous reactions	None identified.
10.4. Conditions to avoid	Prevent contact with strong oxidisers.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Sulphur compounds.

Section 11. Toxicological Information.

11.1. Information on toxicological effects

Acute toxicity: The mixture is not classified for acute toxicity.
Solvent vapours may cause headache, dizziness, nausea and irritation of the respiratory tract.
Xylene and 2-butoxyethanol may cause harmful effects if inhaled or absorbed through the skin, but the mixture does not meet the criteria for acute toxicity classification.

Skin corrosion/irritation:
The mixture is not classified as causing skin corrosion or irritation. Prolonged or repeated contact may cause mild irritation due to surfactant content.

Serious eye damage/eye irritation:
Causes serious eye irritation. Exposure may result in stinging, watering, redness and temporary blurred vision.

Respiratory or skin sensitisation:
May cause an allergic skin reaction (H317). Contains sodium thioglycolate, a known skin sensitiser. Repeated exposure may lead to allergic dermatitis.

Information on other hazards
Surfactants may cause temporary gastrointestinal upset if swallowed.
Product may cause discomfort if inhaled as mist.
No evidence of endocrine disruption.
No additional hazards known under normal conditions of use.

Section 12. Ecological Information.

12.1. Toxicity	Harmful to aquatic life.
12.2. Persistence and degradability	Surfactants biodegradable.
12.3. Bioaccumulative potential	Not expected to bioaccumulate.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	Not applicable.
12.6. Other adverse effects	Prevent release to environment.

Section 13. Disposal Considerations.

13.1. Waste treatment methods
Dispose of in accordance with local authority regulations.
Do not release undiluted product into drains or water courses.

Section 14. Transport Information.

Not classified as hazardous for transport.

Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
No data available.

15.2. Chemical safety assessment
No data available.

Section 16. Additional Information.

Full text of Statements used in Section 3;

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.

The above information is believed to be accurate and represents the best information currently available.
No warranty is expressed or implied by the above information.
We assume no liability resulting from use of the above information.
The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	19/04/2023	First issue.
2	23/10/2026	Section 3

End of Safety Data Sheet.