

# Section 1. Product and Company Identification.

1.1 Model Number; 1.2 Description; SCS222S v1

Thread Lock Low Strength 50ml Unique Formula Identifier (UFI): X73U-G3FH-M109-GAX1

#### 1.3 Manufacturer;

Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 18 February 2015.



# Section 2. Hazards Identification.

**2.1** Classification of the substance or mixture. Irritating to eyes, respiratory system and skin.

2.2 Label elements. Hazard pictogram(s)



Signal Word. Warning

#### Hazard statements;

H315 Causes skin irritation. H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

#### Precautionary statements;

P261: Avoid breathing vapours.

P264: Wash contaminated skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P271: Use only outdoors or in a well-ventilated area.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P332+313: If skin irritation occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

P501: Dispose of contents/container to comply with Local, National and International regulations.

**2.3** Other hazards.

No data available.



# Section 3. Substances.

	3.1 CAS No.	3.2 Concentration Weight	Classification		
3.1 Chemical Name (substance)			Hazard Class & Category Code	Hazard Statements <sup>1</sup>	
Methacrylic Diester of	25852-47-5	30 - 50%	STOT SE 3	H335	
Polyethylene Glycol			Eye Irrit. 2	H319	
			Skin Irrit. 2	H315	
Polyethylene Glycol Bis(2- Ethylexyl) Ether	18268-70-7	10 - 30%	-	-	
Cumene Hydroperoxide	80-15-9	1 - 10%	Org. Perox. E	H242	
			Acute Tox. 3	H331	
			Acute Tox. 4	H312	
			Acute Tox. 4	H302	
			STOT RE 2	H373	
			Skin Corr. 1B	H314	
			Aquatic Chronic 2	H411	
Titanium Dioxide	13463-67-7	1 - 10%	-	-	
Methanol	67-56-1	< 1%	Flam. Liq. 2	H225	
			Acute Tox. 3	H331	
			Acute Tox. 3	H311	
			Acute Tox. 3	H301	
			STOT SE 1	H370	

<sup>1</sup>For full text of Statements, see Section 16.



### Section 4. First Aid Measures.

First Aid measures, general. Call a poison centre or a doctor if unwell. Quote UFI in Section 1.2.

#### **4.1** Description of first aid measures

#### Inhalation

Remove casualty from exposure ensuring one's own safety whilst doing so. Get medical attention if any discomfort continues.

#### Skin Contact

Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

#### Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if any discomfort continues.

#### Ingestion

Wash out mouth with water. Get medical attention if any discomfort continues.

**4.2.** Most important symptoms and effects, both acute and delayed No data available.

- **4.3.** Indication of any immediate medical attention and special treatment needed
- **Skin contact** There may be irritation and redness at the site of contact.
- **Eye contact** There may be irritation and redness. The eyes may water profusely.
- **Ingestion** There may be soreness and redness of the mouth and throat.
- InhalationThere may be irritation of the throat with a feeling of tightness in the chest.<br/>Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### Section 5. Fire Fighting Measures.

**5.1.** Extinguishing media

Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**5.2.** Special hazards arising from the substance or mixture Toxic fumes released during combustion.

5.3. Advice for fire-fightersWear self-contained breathing apparatus.Wear protective clothing to prevent contact with skin and eyes.

# Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency proceduresDo not approach from downwind.Keep bystanders upwind and away from danger point.Mark out the contaminated area with signs and prevent access to unauthorised personnel.Turn leaking containers leak-side up to prevent the escape of liquid.

**6.2.** Environmental precautions Do not discharge into drains, rivers or watercourses. Contain the spillage using bunding.

**6.3.** Methods and material for containment and cleaning up No data available.

6.4. Reference to other sectionsSee Section 7 for information on Safe HandlingSee Section 8 for information of Personal Protective Equipment.See Section 13 for information on disposal.

## Section 7. Handling and Storage.

7.1. Precautions for safe handlingAvoid direct contact with the substance.Ensure there is sufficient ventilation of the area.Do not handle in a confined space.Avoid the formation or spread of mists in the air.

**7.2.** Conditions for safe storage, including any incompatibilities Store in cool, well- ventilated area. Keep container tightly closed.

**7.3.** Specific end use(s) Intended for use as Thread Lock, Model Number identified in 1.1 with Description stated in 1.2.





# Section 8. Exposure Controls/Personal Protection.

#### 8.1. Control parameters

Workplace exposure limits.

		Workplace exposure limit.			mit.
Substance	CAS number	Long term.		Short term.	
		ppm	mg.m <sup>3</sup>	ppm	mg.m <sup>3</sup>
Titanium Dioxide total inhalable	13463-67-7	-	10	-	-
Titanium Dioxide respirable	15405-07-7	-	4	-	-
Methanol	67-56-1	200	266	250	333

#### 8.2. Exposure controls

#### Appropriate Engineering Controls

Use only outdoors or in a well-ventilated area.

#### **Eye/Face Protection**

Safety glasses with side shields or chemical safety goggles. Ensure eye bath is to hand.

#### **Skin Protection**

EN 374 Chemical resistant protective gloves. Wear suitable protective clothing.

#### **Respiratory Protection**

Avoid breathing vapours. Self-contained breathing apparatus must be available in case of emergency.



# Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties The following information is not a technical specification or sales specification. (a) Appearance: White liquid. (b) Odour: Barely perceptible. (c) Odour threshold; No data available. (d) pH: Not relevant. (e) Melting point/freezing point; Not relevant. (f) Initial boiling point and boiling range; > 35 °C > 93 °C (g) Flash point; (h) Evaporation rate; No data available. (i) Flammability (solid, gas); No data available. (j) Upper/lower flammability or explosive limits; No data available. (k) Vapour pressure; <= 666.6 No data available. (I) Vapour density; (m) Relative density; 1.17 (n) Solubility(ies); Insoluble in water. (o) Partition coefficient: n-octanol/water; No data available. (p) Auto-ignition temperature; No data available. (q) Decomposition temperature; No data available. (r) Viscosity; No data available. (s) Explosive properties; No data available. No data available. (t) Oxidising properties. 9.2 Other information No data available.

## Section 10. Stability and Reactivity.

10.1. Reactivity 10.2. Chemical stability 10.3. Possibility of hazardous reactions

10.4. Conditions to avoid 10.5. Incompatible materials 10.6. Hazardous decomposition products Stable under recommended transport or storage conditions. Stable under normal conditions.

Hazardous reactions will not occur under normal transport storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

Heat

Strong oxidising agents. Strong acids. In combustion emits toxic fumes.



## Section 11. Toxicological Information.

**11.1.** Information on toxicological effects Hazardous Ingredients:

CUMENE HYDROPEROXIDE

ORL	MUS	LDLO	5	gm/kg
ORL	RAT	LD50	382	mg/kg
SCU	Rat	LD50	382	mg/kg

#### Methanol

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Opt - Optical Inh - Inhalation Drm - Dermal

#### **Relevant effects for mixture:**

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

# Section 12. Ecological Information.



Hazardous ingredient	ts			
TITANIUM DIOXIDE				
FISH	96H LC50	1000000	μg/l	
12.2. Persistence and	l degradability	No data available.		
12.3. Bioaccumulative potential		No data available.		
12.4. Mobility in soil		No data available.		
12.5. Results of PBT and vPvB assessment		This product is not identified as a PBT/vPvB substance.		
12.6. Other adverse effects		No data available.		

### Section 13. Disposal Considerations.

13.1. Waste treatment methods

Dispose of in accordance with local authority regulations.

### Section 14. Transport Information.

<b>14.1.</b> UN number	UN 3082
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s.
	(Cumene hydroperoxide)
14.3. Transport hazard class	9
14.4. Packing group	III
14.5. Environmental hazards	Toxic to aquatic life with long lasting effects.
14.6. Special precautions for user	No special precautions necessary.

<u>ADR - Agreement Concerning the International Carriage of Dangerous Goods by Road</u> Special provision 375: Packagings must meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. No other provisions of ADR apply.

<u>IATA DGR - International Air Transport Association Dangerous Goods Regulations</u> Special provision A197: Packagings must meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. No other provisions of IATA DGR apply.

<u>IMDG Code</u> - International Maritime Dangerous Goods Code Special provision 375: Packagings must meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. No other provisions of the IMDG Code apply.

# Section 15. Regulatory Information.

**15.1.** Safety, health and environmental regulations/legislation specific for the substance or mixture No data available.

**15.2.** Chemical safety assessment No data available.

## Section 16. Additional Information.

Full text of Statements used in Section 3;

H225 Highly flammable liquid and vapour.

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available. No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	08/04/2016	First issue.
2	22/03/2017	Format Only.
3	29/04/2019	Section 14
4	17/02/2021	Section 2.2
5	14/01/2025	Section 1.2 Section 4
6	31/01/2025	Section 14

End of Safety Data Sheet.



