Section 1. Product and Company Identification.

1.1 Model Number; SPB101 v1

1.2 Description; Portable Power Bank 10W 10000mAh

Battery: 3.7 Volts. 10 Ah. 175.7 grams.



Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 1st January 2022

Section 2. Hazards Identification.

Battery is hermetically sealed and does not present a hazard under normal conditions of use. Inappropriate handling and / or use can cause electrolyte to leak.

Ingestion: Contents of an open battery can cause chemical burns of mouth, oesophagus, and gastrointestinal

tract.

Inhalation: Contents of an open battery can cause respiratory irritation.

Skin Contact: Contents of an open battery can cause skin irritation. **Eye Contact:** Contents of an open battery can cause irritation.





Section 3. Substances.

3.1 Chemical Name (substance)	3.1 CAS No.		Classification	
		3.2 Concentration Weight	Hazard Class &	Hazard
			Category Code	Statements ¹
Li/NiCoMax\Q2		No Data Available	_	
Li(NiCoMn)O2	7420.06.5	No Data Available		
Manganese	7439-96-5		-	
Graphite	7782-42-5	No Data Available	-	
Six Fluorine Iron Lithium	21324-40-3	No Data Available	-	
Copper Foil	7440-50-8	No Data Available	Aquatic Chronic 2	H411
Aluminum Foil	7429-90-5	No Data Available	Pyr. Sol. 1	H250
			Water-react. 2	H261
Nickel	7440-02-0030	No Data Available	-	
Lead	7439-92-1	No Data Available	Repr. 1A	H360FD
			Lact.	H362
			Aquatic Acute	H400
			1	H410
			Aquatic	
			Chronic 1	
Cadmium	7440-43-9	No Data Available	Carc. 1B	H351
			Muta. 2	H331
			Repr. 2	H301
			Acute Tox. 2	H373
			STOT RE 1	H400
			Aquatic Acute	H410
			1	
			Aquatic	
			Chronic 1	
Mercury	7439-97-6	No Data Available	Repr. 1B	H360D
			Acute Tox. 2	H330
			STOT RE 1	H372
			Aquatic Acute	H400
			1	H410
			Aquatic	
			Chronic 1	

¹For full text of Statements, see Section 16.



Section 4. First Aid Measures.

Lithium Batteries do not pose a risk to eyes or skin under normal circumstances. In the case of contact with internal substances;

4.1 Description of first aid measures

Inhalation

If breathing difficulties develop, remove the person to fresh air.

Loosen close fitting clothing.

Ensure that person is warm.

If mouth to mouth resuscitation is necessary, the person conducting this must takes steps to reduce the risk of contamination from toxic / corrosive substances that may be present.

Skin Contact

Remove contaminated clothing.

Flush affected area(s) with copious amounts of water for at least 15 minutes.

Get medical attention.

Eye Contact

Irrigate eyes with water for at least 15 minutes while raising eyelid(s).

Get medical attention.

Ingestion

If swallowed, do not induce vomiting. Give large amounts of water but do not do this if casualty is unconscious.

Protection of First Aiders:

Use personal protective equipment. Avoid contact with skin, eyes and clothing.

4.2. Most important symptoms and effects, both acute and delayed No data available.

4.3. Indication of any immediate medical attention and special treatment needed No data available.



Section 5. Fire Fighting Measures.

Recommended practice;

Always ensure that Personal Protection Equipment (PPE) is used.

If a battery becomes hot, immediately remove it from flammable materials and place on a non-combustible surface. If possible, place a disintegrating device outdoors and allow it to burn out.

Fire condition; NB; ensure that electrical devices are turned off. Prevent electric shock risk.

If any batteries are burning, water may not extinguish them, but will cool the adjacent batteries and control the spread of fire.

5.1. Extinguishing media

Extinguishers;

Only use Graphite based CO₂ (Carbon dioxide), Dry Powder or Foam.

Copper powder fire extinguishers, sand, dry ground dolomite or soda ash may also be used. These materials act as smothering agents.

If possible, use a **LITH-X** (**powdered graphite**) extinguisher on small fires. This material acts as a smothering agent. A **sodium chloride powder** extinguisher **IS NOT** suitable for use on Lithium Batteries.

It may not be possible to extinguish burning lithium batteries. Burning batteries will burn themselves out. <u>Do not use water</u> with **LITH-X (powdered graphite)**.

If a LITH-X (powdered graphite) extinguisher is not available;

Use copious amounts of water in a fine spray to swamp a fire.

Continue to use copious amounts of water until the fire is extinguished and the batteries are cooled.

NB: Lithium reacts with water to form Hydrogen. The fire will not be extinguished immediately.

Be aware of the increased risk of explosion.

NB; fire-fighting water runoff may be corrosive / toxic and may cause adverse environmental impact.

5.2. Special hazards arising from the substance or mixture

Hazard characteristics; thermal decomposition can lead to the release of toxic fumes.

Hazardous combustion products; carbon dioxide, carbon monoxide, lithium oxide fumes.

5.3. Advice for fire-fighters

Fragments may be ejected from a fire.

Fire Fighters should wear self-contained breathing apparatus and appropriate Personal Protective Equipment.



Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures In the event of battery rupture and leakage,

- ventilate the area.
- wear appropriate protective clothing (see Section 8) to prevent eye and skin contact and to prevent inhalation of vapours or fumes.
- remove sources of ignition.

6.2. Environmental precautions

No data available.

6.3. Methods and material for containment and cleaning up

Absorb released materials with inert absorbent (dry sand or soil).

Collect released materials into sealed plastic bag or container.

Prevent material from contaminating soil or entering sewers or waterways.

Do not dispose of released materials with domestic waste

Do not allow product to enter ground water, water course or sewerage system.

Dispose of released materials in accordance with local authority regulations.

6.4. Reference to other sections

See Section 7 for information on Safe Handling

See Section 8 for information of Personal Protective Equipment.

See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling

Never dismantle or modify a battery.

Do not short circuit a battery. A short circuit causes heating and can lead to ignition of surrounding materials.

Physical contact with a short-circuited battery can cause skin burn.

When charging the battery, use dedicated chargers and follow the specified conditions.

Improperly charging a battery may cause the battery to combust.

Lithium batteries for transport by air in a state of charge must have no more than 30% charge of their rated capacity.

7.2. Conditions for safe storage, including any incompatibilities

Prevent contact with conductive materials.

Do not allow contact with water.

Store in original container. Keep container tightly closed.

Store in a dry, cool place.

Store at 20 °C (68°F); room temperature

Store away from ignition sources, heat, and incompatible materials.

7.3. Specific end use(s)

Intended for use as the battery for the Model Number identified in 1.1 with Description stated in 1.2



Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters

In the event of battery rupture and leakage:

Ventilate the area.

Remove sources of ignition.

8.2. Exposure controls

The use of Personal Protective Equipment (PPE) is not necessary under conditions of normal use.

If handling a leaking or ruptured battery, ensure that the following Personal Protective Equipment (PPE) is used.

Eye/Face Protection

Chemical grade full face shield

Skin Protection

Acid resistant, natural rubber or neoprene gloves.

Protective rubber apron

Appropriate Personal Protection with long sleeves and long trousers.

Respiratory Protection

Acid gas filter mask or self-contained breathing apparatus.

Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance: Prism

(b) Odour:(c) Odour threshold;If leaking, smells of medical ether.Not relevant to battery as supplied.

(d) pH: No applicable as supplied.

(e) Melting point/freezing point; Not relevant. (f) Initial boiling point and boiling range; Not relevant.

(g) Flash point; Not applicable unless individual components exposed.

(h) Evaporation rate; No data available.

(i) Flammability (solid, gas); Not applicable unless individual components exposed.

(j) Upper/lower flammability or explosive limits;
 (k) Vapour pressure;
 (l) Vapour density;
 No data available
 No data available

(m) Relative density; Not applicable unless individual components exposed. (n) Solubility(ies); Not applicable unless individual components exposed.

(o) Partition coefficient: n-octanol/water;
 (p) Auto-ignition temperature;
 (q) Decomposition temperature;
 (r) Viscosity;
 (s) Explosive properties;
 (t) Oxidising properties.
 No data available
 No data available
 No data available

9.2 Other information No data available



Section 10. Stability and Reactivity.

10.1. Reactivity No data available

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid Mechanical shock.

Vibrations during transport are not detrimental to condition.

Do not dismantle, crush or install with incorrect polarity.

Prevent mechanical / electrical misuse.

Acids, Oxidizing agents, and Bases

Carbon Oxides

Section 11. Toxicological Information.

11.1. Information on toxicological effects

10.6. Hazardous decomposition products

Potential health risks;

10.5. Incompatible materials

Eye; Contact with battery contents may cause severe irritation and burns. Eye damage is possible.

Skin; Contact with battery contents may cause severe irritation and burns.

Absorption through the skin will cause localized inflammation.

Ingestion; may cause severe and permanent damage to the digestive tract. May cause circulatory system failure. Contents of an open battery can cause serious chemical burns to the mouth, oesophagus and gastrointestinal tract. **Inhalation**; Inhalation of vapours or fumes released due to heat or leaking batteries may cause respiratory irritation. Irritation may lead to chemical pneumonitis.

Inhalation can produce chronic productive cough and shortness of breath.

Section 12. Ecological Information.

When properly used and disposed of correctly, the battery does not present environmental hazard. Do not release internal components into water ways, wastewater or ground water.

Section 13. Disposal Considerations.

Disposal of the battery must be in accordance with local authority regulation requirements for hazardous waste treatment and hazardous waste transportation.

The battery should be completely discharged prior to disposal and the terminals taped or capped to prevent short circuit.

Do not dispose of batteries at landfill sites.

Do not incinerate batteries.



Section 14. Transport Information.

ADR. International Carriage of Dangerous Goods by Road.

14.1. UN number UN 3481

14.2. Name and Description Lithium ion batteries contained in equipment

14.3. Transport hazard class(es) 9

14.4. Packing group -

14.5. Environmental hazards Does not present an environmental hazard.

14.6. Special precautions for user No special precautions necessary.

IATA. International Air Transport Association.

14.1. UN number UN 3481

14.2. UN Proper Shipping Name/Description Lithium ion batteries contained in equipment

14.3. Transport hazard class(es) **9. 14.4.** Packing group

14.5. Environmental hazards Does not present an environmental hazard.

14.6. Special precautions for user No special precautions necessary.

IMDG. International Maritime Dangerous Goods.

14.1. UN number UN 3481

14.2. UN proper shipping name Lithium ion batteries contained in equipment

14.3. Transport hazard class(es) Class or Division

14.4. Packing group -

14.5. Environmental hazards Does not present an environmental hazard.

14.6. Special precautions for user No special precautions necessary.

14.7. Transport in bulk – Maritime only.

Bulk transport is not applicable to this product

Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture No data available.

15.2. Chemical safety assessment

No data available.



Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

H250 Catches fire spontaneously if exposed to air.

H261 In contact with water releases flammable gases.

H301 Toxic if swallowed.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H362 May cause harm to breast-fed children.

H372 Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available. No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	06/05/2022	First issue.
2	21/09/2022	Section 3

End of Safety Data Sheet.