

Section 1. Product and Company Identification.

1.1 Model Number; & 1.2 Description;

	· · ·
WED1025 v1	Welding Electrodes Dissimilar Ø2.5 x 350mm 1kg Pack
WED1032 v1	Welding Electrodes Dissimilar Ø3.2 x 350mm 1kg Pack
WED1040 v1	Welding Electrodes Dissimilar Ø4 x 350mm 1kg Pack
WED5025 v1	Welding Electrodes Dissimilar Ø2.5 x 350mm 5kg Pack
WED5032 v1	Welding Electrodes Dissimilar Ø3.2 x 350mm 5kg Pack
WED5040 v1	Welding Electrodes Dissimilar Ø4 x 350mm 5kg Pack

1.3 Manufacturer;

Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500

Date of source compilation; 15/04/2012

Section 2. Hazards Identification.



T: Toxic

Risk phrases;

- R23 Toxic by inhalation.
- R40 Limited evidence of a carcinogenic effect.
- R43 May cause sensitisation by skin contact.
- R48 Danger of serious damage to health by prolonged exposure.

Safety phrases;

- S 24 Avoid contact with skin
- S 36 Wear suitable protective clothing
- S 37 Wear suitable gloves

Section 3. Substances.



3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Percentage of Content (mixture)	See Section 16
Chromium (Chromium)	7440-47-3	30 - 40%	
nickel powder	7440-02-0	10 - 20%	Carc. Cat. 3;
			R40 T; R48/23
			R43 R52-53
Limestone (Calcium carbonate	1317-65-3	5 - 10%	
total inhalable dust)			
Kaolin (Kaolin, respirable dust)	1332-58-7	5 - 10%	
Silicic acid, calcium salt (Calcium	1344-95-2	5 - 10%	
silicate total inhalable dust)			
Silicic acid, aluminium potassium	1327-44-2	5 - 10%	
salt			
Manganese	7439-96-5	1 - 10%	
Silicon (Silicon total inhalable	7440-21-3	1 - 10%	
dust)			
Cellulose (Cellulose (pure) total	9004-34-6	0.5 - 1%	
inhalable dust)			
Copper (Copper fume)	7440-50-8	0.5 - 1%	
Molybdenum	7439-98-7	0.5 - 1%	
Carbon (Graphite total inhalable	7440-44-0	0 - 0.5%	
dust)			
Phosphorus, red (Phosphorus,	7723-14-0	0 - 0.5%	F; R11 R16 R52-53
yellow)			
sulphur	7704-34-9	0 - 0.5%	Xi; R38



Section 4. First aid measures.

Inhalation Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
 Eye contact Avoid contact with eyes. Seek medical attention
 Skin contact Wash off immediately with plenty of soap and water.
 Ingestion If swallowed, seek medical advice immediately and show the container or label.

Section 5. Fire Fighting Measures.

5.1. Extinguishing media
Carbon dioxide (CO2). Dry chemical.
For large fires: Alcohol resistant foam. Water jet.
5.2. Special hazards arising from the substance or mixture
No data available.
5.3. Advice for fire-fighters
Self-contained breathing apparatus.
Wear suitable respiratory equipment when necessary.

Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Ensure adequate ventilation of the working area.

Refer to Exposure Controls in Section 8

6.2. Environmental precautions

No data available.

6.3. Methods and material for containment and cleaning up

Sweep up. No specific clean up requirements. Refer to disposal considerations in Section 13.

Section 7. Handling and Storage.

7.1. Precautions for safe handling

Wear suitable gloves. See Section 8 Exposure Controls.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed and dry.

Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters Carbon (Graphite respirable) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/m3: Carbon (Graphite total inhalable dust) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: Cellulose (Cellulose (pure) respirable) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: Cellulose (Cellulose (pure) total inhalable dust WEL 8-hr limit mg/ m3: WEL 15 min limit mg/m3: Chromium (Chromium) WEL 8-hr limit mg/ m3: 0.5 WEL 15 min limit mg/ m3: Copper (Copper dusts and mists (as Cu)) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/m3: Copper (Copper fume) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/m3: Kaolin (Kaolin, respirable dust) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: WEL 8-hr limit mg/ m3: Limestone (Calcium carbonate respirable) WEL 15 min limit mg/m3: Limestone (Calcium carbonate total inhalable dust) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: WEL 8-hr limit mg/ m3: Limestone (Limestone respirable) WEL 15 min limit mg/ m3: Limestone (Limestone total inhalable) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: Limestone (Marble respirable) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: WEL 8-hr limit mg/ m3: Limestone (Marble total inhalable) WEL 15 min limit mg/m3: Phosphorus, red (Phosphorus yellow) WEL 8-hr limit mg/ m3: 0.1 WEL 15 min limit mg/ m3: 0.3 Silicic acid, calcium salt (Calcium silicate respirable) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: Silicic acid, calcium salt (Calcium silicate total inhalable dust) WEL 8-hr limit mg/ m3: WEL 15 min limit mg/ m3: WEL 8-hr limit mg/ m3: Silicon (Silicon respirable dust) WEL 15 min limit mg/m3: Silicon (Silicon total inhalable dust) WEL 8-hr limit mg/ m3:



4

_

10

4

_

10

20

_

1

2

2

_

4

_

_

4

_

10

4

_

_

4

_

10

3

4

_

_

WEL 15 min limit mg/ m3:

10

10

10

0.2

8.2. Exposure controls





Keep away from foodstuffs, beverages and feed.

Use appropriate personal protective equipment.

Wear suitable protective clothing and eye/face protection.

Wear suitable gloves.

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

(a) Appearance:	solid, brown.
(b) Odour:	characteristic
(c) Odour threshold;	no data available
(d) pH:	no data available
(e) Melting point/freezing point;	no data available
(f) Initial boiling point and boiling range;	no data available
(g) Flash point;	no data available
(h) Evaporation rate;	no data available
(i) Flammability (solid, gas);	no data available
(j) Upper/lower flammability or explosive limits;	no data available
(k) Vapour pressure;	no data available
(l) Vapour density;	no data available
(m) Relative density;	no data available
(n) Solubility(ies);	no data available
(o) Partition coefficient: n-octanol/water;	no data available
(p) Auto-ignition temperature;	no data available
(q) Decomposition temperature;	no data available
(r) Viscosity;	no data available
(s) Explosive properties;	no data available
(t) Oxidising properties.	no data available

Section 10. Stability and Reactivity.

10.1. Reactivityno data available10.2. Chemical stabilitystable under normal conditions.10.3. Possibility of hazardous reactionsno data available10.4. Conditions to avoidno data available10.5. Incompatible materialsno data available10.6. Hazardous decomposition productsnone

Section 11. Toxicological Information.

May cause irritation to skin in susceptible persons.

May cause sensitisation by inhalation. Inhalation may cause nausea and vomiting. May cause drowsiness or dizziness.

Section 12. Ecological Information.

Do not release into the environment.

Section 13. Disposal Considerations.

Disposal of material and container must be in accordance with local authority regulation requirements.

Section 14. Transport Information.

The product is not classified as dangerous for carriage.

Section 15. Regulatory Information.

No data available

Section 16. Additional Information.

Text of Risk Phrases in Section 3

- R11 Highly flammable.
- R16 Explosive when mixed with oxidizing substances.
- R23 Toxic by inhalation.
- R38 Irritating to skin.
- R40 Limited evidence of a carcinogenic effect.
- R43 May cause sensitisation by skin contact.
- R48 Danger of serious damage to health by prolonged exposure.
- R52 Harmful to aquatic organisms.
- R53 May cause long-term adverse effects in the aquatic environment.

The above information is believed to be accurate and represents the best information currently available. No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.